

DHC-E 8/10

COMPACT INSTANTANEOUS WATER HEATER

PRODUCT-NO.: 224201

The electronic compact instantaneous water heater DHC-E reliably supplies one or more draw-off points. Up to the output limit, hot water always flows at precisely the required temperature. The electronic control ensures that the appliance output adjusts automatically subject to the temperature of the water supply and the selected DHW temperature. The DHW temperature is variably adjustable. The tubular heater system with pressure-tested copper casing is suitable for soft water areas.



The main features

For one or several draw-off points

Constant temperature up to the output limit

Simple and secure operation

Easy and quick installation

Works even with low water pressure

ETL compliant

Splashproof to IP 24



Type	DHC-E 8/10	DHC-E 12
Part no.	224201	230628
Rated output	7,2/9,6 kW	12 kW
Height	360 mm	360 mm
Width	200 mm	200 mm
Depth	110 mm	110 mm

Technical data

Rated voltage 1	208 V	208 V
Rated output 1	5,4/7,2 kW	9 kW
Rated current 1	28/35 A	44 A
Fuse 1	30/50 A	60 A
Rated voltage 2	220 V	220 V
Rated output 2	6,0/8,1 kW	10 kW
Rated current 2	30/50 A	46 A
Fuse 2	40/50 A	60 A
Rated voltage 3	230 V	230 V
Rated output 3	6,6/8,8 kW	11 kW
Rated current 3	31/39 A	48 A
Fuse 3	40/50 A	60 A
Phases	1/N/PE ~220-240V	1/N/PE ~220-240V
Frequency	50/60 Hz	50/60 Hz
Temperature adjustment	30-60 °C	30-60 °C
Energy efficiency class	A	A
IP-Rating	IP24	IP24
Colour	white	white

Weight

2,70 kg

2,70 kg

Contact information

You have questions? We appreciate to help you:

Call **+49 5531 - 7020**

Write an email to **info@stiebel-eltron.com**

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.