



Catalog Number
Notes
Type

Contractor Select™
CNY LED
 Canopy Lighting



The CNY LED canopy luminaire is a versatile and energy efficient solution for replacing up to 400W HID luminaires. Delivering up to 13,900 lumens, CNY LED provides a great, cost effective canopy lighting solution. Quick mount feature eliminates the need to open luminaire for installation - saves time and money.

FEATURES:

- Replaces: Up to 400W HID lamps, saves 80% energy
- Quick mount feature eliminates the need to open luminaire for installation - saves time and money
- Expected service life over 10 years - no maintenance costs and hassles



Catalog Number	UPC	Description	Replaces Up To	Lumens	Wattage	CCT	Voltage	Finish	Pallet qty.
CNY LED P1 40K MVOLT DDB	191848093320	WALL PACKS	400W METAL HALIDE	4,500	35W	4000K	120-277V	DARK BRONZE	60
CNY LED P1 40K MVOLT WH	191848112076	WALL PACKS	400W METAL HALIDE	4,500	35W	4000K	120-277V	WHITE	60
CNY LED P2 40K MVOLT DDB	191848093344	WALL PACKS	400W METAL HALIDE	6,600	52W	4000K	120-277V	DARK BRONZE	60
CNY LED P3 40K MVOLT DDB	191848093443	WALL PACKS	400W METAL HALIDE	11,000	86W	4000K	120-277V	DARK BRONZE	60



Specifications

INTENDED USE:

CNY LED luminaires are ideal for energy-efficient replacement of up to 400W Metal Halide canopy/ceiling lights. Traditional style does not detract from current building aesthetics. The CNY LED provides years of maintenance-free general illumination for outdoor applications. Ideal for entrances, parking areas, covered walkways and loading docks.

CONSTRUCTION:

Cast-aluminum, corrosion-resistant housing with bronze polyester powder paint for lasting durability. Castings are sealed with a one-piece gasket to inhibit the entrance of external contaminants. Rated for outdoor installations, -40°C minimum ambient. Acrylic lens is designed for uniform light distribution.

ELECTRICAL:

Includes an MVOLT (120-277V) driver. LEDs maintain 70% of light output at 100,000 hours of service life (L70/100,000 hours).

INSTALLATION

Mounts to a recessed junction box or surface mount with three conduit entry points. Can be pendant mounted with 3/4" NPT pendant stem provided by others. Quick mount mechanism significantly reduces installation time.

LISTINGS:

UL Listed to U.S. and Canadian safety standards for wet locations. Tested in accordance with IESNA LM-79 and LM-80 standards. DesignLights Consortium® (DLC) Premium qualified product and DLC qualified product. Not all versions of this product may be DLC Premium qualified or DLC qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.

WARRANTY:

5-year limited warranty. Complete warranty terms located at:

www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.


Dimensions

CNY LED P1/P2

Width: 10"

Height: 4.5"

Depth: 10"





CNY LED P3/P4

Width: 14"

Height: 6"

Depth: 14"



All dimensions are inches (centimeters) unless otherwise indicated.