TECHNICAL SPECIFICATIONS





Stainless Steel Braided Water Connectors

For Toilet (EF-TC-Series)

Reliable braided water connectors for Toilet connection. Easyflex flexible braided water connectors provide protection from vibration and bursting under extreme pressure surge. Reinforced PVC hose braided with stainless steel are durable and all lead-free certified.

FEATURES

- Durable, flexible water connector with reinforced PVC inner hose, braided with stainless steel.
- Chrome plated brass hex nuts for corrosion resistance.
- Reliable nut-to-hose connection with sturdy pneumatic crimp.
- EPDM washer provides safe and reliable water tight sealing.

MATERIALS

Braided Jacket	Stainless Steel 304 (ASTM A240)		
Inner Hose	Reinforced durable PVC		
Fittings	Anti-corrosion Chrome-Plated Brass		
Washer	EPDM		
Ferrule	Zinc-plated steel		

SPECIFICATIONS

Max. Working Temperature	180°F (82°C)
Max. Working Pressure	125psi (8.6 bar)

DESIGN CERTIFICATIONS AND APPROVALS

• NSF 372 Compliant : Lead-Free

• ASME A 112.18.6-2009 / CSA B 125.6-2009





Job Name :	Engineer / Architect :
Job Location :	Wholesaler:
Submittal Date :	Contractor:



Stainless Steel Braided Water Connectors

for Toilet (EF-TC-Series)

lmana	Devt #	Description		Ob. / Davi
Image	Part #	Hose & Fittings	Length	Qty / Box
	EF-TC-38CBC-9	TC SS Braided Toilet Connector 3/8" Compression x 7/8" Ballcock	9"	50
	EF-TC-38CBC-12		12"	50
	EF-TC-38CBC-16		16"	50
	EF-TC-38CBC-20		20"	50
	EF-TC-38CMBC-12	TC SS Braided Toilet Connector 3/8" Compression	12"	50
	EF-TC-38CMBC-16		16"	50
	EF-TC-38CMBC-20	x 7/8" Metal Ballcock	20"	50
	EF-TC-12FBC-12	TC SS Braided Toilet Connector 1/2" FIP	12"	50
	EF-TC-12FBC-16		16"	50
	EF-TC-12FBC-20	x 7/8" Ballcock	20"	50