KOHLER_®

Kingston™ Ultra

Top spud antimicrobial flushometer bowl w/ bedpan lugs

K-84325-SSL

Features

- Elongated bowl offers added room and comfort.
- Siphon jet.
- 1.0 gpf (3.8 lpf), 1.1 gpf (4.2 lpf), 1.28 (4.8 lpf), or 1.6 gpf (6.0 lpf) depending on flushometer specified.
- 11" x 8-1/4" (279 mm x 210 mm) water surface.
- Bedpan lugs included.
- Antimicrobial finish inhibits the growth of mold-, mildew-, stain-, and odor-causing bacteria on the fixture surface. This product does not protect users against bacteria, viruses, or other disease organisms. Always clean and wash this product thoroughly before and after each use.
- 1-1/2" (38 mm) top spud.

Material

Vitreous china.

Technology


- Improved flush for toilet seat cover removal.
- Re-engineered for strong flush performance in buildings with lower water pressure or flow.
- Cast-on putty plate resists breakage.
- New design eliminates gas leaks, splashing and paper shredding.

Installation

- Wall-mount.
- This product replaces K-4325-SSL.

Included Components

Additional Components: Bedpan lugs





Codes/Standards

ASME A112.19.2/CSA B45.1 DOE - Energy Policy Act 1992 California Energy Commission (CEC) ADA ICC/ANSI A117.1 CSA B651 OBC

KOHLER[®] One-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color Code Description

0 White





Kingston™ Ultra Top spud antimicrobial flushometer bowl w/ bedpan lugs K-84325-SSL

For Back-to-Back Toilet Installations O Use a 45° double Do not use a wye fitting. double sanitary tee. 1/16" 15-9/16" (2 mm) 25-13/16" (656 mm) (395 mm) 2-3/4" 9" (229 mm) (70 mm) 1-1/2" Spud 1-3/4" 2-1/2" (44 mm) (64 mm) 7-1/2" 13-1/4" 15" (191 mm) (337 mm) (381 mm) 5"

Technical Information

5"

(127 mm)

All product dimensions are nominal. Toilet type: Wall-mount Waste Outlet: Wall Flush type: Flushometer valve siphon Spud size: 1 1/2, Inlet, Top Trap passageway: 2-1/8" (54 mm) Water Consumption Full: 1.6 gpf (6 lpf) Reduced: 1 gpf (3.8 lpf) Water surface size: 11" x 8-1/4" (279 mm x 210 mm) Rim to water 5-13/16" (148 mm) surface: Seat-mounting 5-1/2" (140 mm) holes:

£ of Outlet

Fixture Supply Requirements

Min static pressure:	35 psi (241.3 kPa)
Max static pressure:	80 psi (551.6 kPa)
Min flowing	25 psi (172.4 kPa)

Notes

(127 mm)

Install this product according to the installation instructions.

For back-to-back toilet installations: Use only a 45° double wye fitting.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.

Plumbing codes may require elongated toilets and elongated, open-front seats in public bathrooms.

Accessibility standards may require controls to be located on the open side of the toilet.

1-800-4KOHLER (1-800-456-4537) Kohler Co. reserves the right to make revisions without notice to product specifications. For the most current Specification Sheet, go to <u>www.kohler.com</u>. 7-19-2022 21:44 - US

