

Rainier™ Trim and Shower Combination (Valve not included)

FEATURES:

- CPT-8001-P: Shower Valve Trim
- S-3018: 2.5 GPM (9.5 L/min Flow Rate Shower Head
- S-2550: Shower Arm and Flange



VALVE OPTIONS:

- CPV-PB: Pressure Balance Valve
Sweat & Thread Connections
- CPV-PB-PXC: Pressure Balance Valve
PEX F1807 Crimp Inlet Connections
- CPV-PB-PXE: Pressure Balance Valve
PEX F1960 Cold-Expansion Inlet Connections
- CPV-T: Thermostatic Valve
Sweat & Thread Connections
- CPV-T-PXC: Thermostatic Valve
PEX F1807 Crimp Inlet Connections
- CPV-T-PXE: Thermostatic Valve
PEX F1960 Cold-Expansion Inlet Connections



STOCK FINISHES:



PC

STANDARDS:

- ASME A112.18.1/CSA B125.1 certified

WARRANTY:


Visit www.speakman.com for full product warranty information

- See Speakman.com For Warranty Information



Information continues on next page

Rainier™ Trim and Shower Combination (Valve not included)



DIMENSION	CPV-PB	CPV-T	CPV-PB-PXC	CPV-PB-PXE	CPV-T-PXC	CPV-T-PXE
A	7/16" (11mm)	1/2" (12mm)		7/16" (11mm)		1/2" (12mm)
B	3-5/16" (84mm)	3-1/2" (89mm)		3-5/16" (84mm)		3-1/2" (89mm)
C	4-13/16" (123mm)	5-7/8" (150mm)		4-13/16" (123mm)		5-7/8" (150mm)
D	2-1/2" (63mm) MIN TO 3-1/2" (89mm) MAX					
E		3-1/8" (79mm) MIN TO 4-1/8" (105mm) MAX			3-3/16" (81mm) MIN TO 4-3/16" (106mm) MAX	