14540S-15: 6in Traverse Lyte Round T24 3000K 90CRI Dimensions:

White





Diameter: 7 3/8"

Height: 1 1/16"

Weight: 0.65 lbs.

Wire: 6 1/2" (color/Black/White)

Connection: Mounted To Box

Bulb Type: Modules

Bulb Base: Integrated

Volts: 120 **Watts:** 13

Watts Consumed: 13

Watts Rated: 13

Hours Rated: 50000

Lumens: 850

Bulb Temp: 3000 °K

CRI: 90



Collection: Traverse LED Lyte

Dimming range: 5%-100%

Retrofit Kit 14795 may be purchased separately in 10pc sets.

Gasket 620390 may be purchased separately in 10pc sets.

UPC #:785652073212

Finish: White (15)

Bulbs:

1 - LED Integrated Modules 13w Max. 120v - included

Features:

- · Fixture may be mounted on wall or ceiling.
- Product complies with NEC 410.16 code and is closet rated.
- ENERGY STAR® Qualified
- This fixture is classified as a directional light source
- This advanced LED technology is carefully designed and selected to consist of the highest quality LED chipsets for superior performance and reliability.
- Meets Title 24 energy efficiency standards
- Integrated LED fixtures that meet the high efficacy LED standards set forth in Title 24 and are listed in the California Energy Commission Appliance database.

Material List:

1 Housing - Aluminum - White 1 Trim - Aluminum - White

Safety Listing:

Safety Listed for Wet Locations

Instruction Sheets:

Trilingual (English, Spanish, and French) (990TRAVLYTE56T24) Trilingual (English, Spanish, and French) (990TRAVLYTE56)

Shade / Glass / Diffuser Details:

Part	Material	Finish	Quantity	Item Number	Length	Width	Height	Diameter	Fitter Diameter	Shade Top Length	Shade Top Width	Shade Top Diameter
Lens	Acrylic	Frosted	1				1/4	4				

Shipping Information:

Package Type	Product #	Quantity	UPC	Length	Width	Height	Cube	Weight	Frt. Class	UPS Ship
Individual	14540S-15	1	785652073212	7.75	7.75	1.5	0.052	0.7	85	Yes
Master Pack	14540S-15	20	10785652073219	16.25	16.25	8.75	1.337	15.3	85	Yes
NJ Pallet		960		48	40	74.25	82.5	734		No
NV Pallet		960		48	40	75	83.333	732		No