



Thin gauge, high performance cast hand film

Cling

- Differential, one-sided cling

Common Applications

- Manual warehouse applications
- A, B, and C loads

Characteristics

- Clear film
- Quiet and easy unwinding from the roll
- Film stiffness provides high load containment

Selling Applications

- Excellent film to replace standard grade films



| Product Code | JDE # | Gauge | Microns | Width (in) | Length (ft) | LBS per Roll | LBS per Case | Rolls per Case | Cases Per Pallet |
|--------------|---------|-------|---------|------------|-------------|--------------|--------------|----------------|------------------|
| XH102161968 | 1645505 | 40 | 10.2 | 16.0 | 1968 | 5.04 | 20.16 | 4 | 48 |
| XH107111968 | 1645514 | 42 | 10.7 | 11.0 | 1968 | 3.64 | 14.56 | 4 | 60 |
| XH107161968 | 1645545 | 42 | 10.7 | 16.0 | 1968 | 5.29 | 21.16 | 4 | 48 |
| XH107181476 | 1645625 | 42 | 10.7 | 18.0 | 1476 | 4.46 | 17.84 | 4 | 48 |
| XH1201281476 | 1650588 | 47 | 12.0 | 12.8 | 1476 | 3.55 | 14.20 | 4 | 60 |
| XH120161476 | 1645631 | 47 | 12.0 | 16.0 | 1476 | 4.44 | 17.76 | 4 | 48 |
| XH120161968 | 1645633 | 47 | 12.0 | 16.0 | 1968 | 5.92 | 23.68 | 4 | 48 |
| XH120181476 | 1645678 | 47 | 12.0 | 18.0 | 1476 | 4.99 | 19.96 | 4 | 48 |
| XH150161476 | 1645692 | 59 | 15.0 | 16.0 | 1476 | 5.57 | 22.28 | 4 | 48 |

For more information, call us at 1.877.662.3779 or visit berryglobal.com



XH® is a trademark of Berry Global, Inc. or one of its affiliates.