



Compact Series Camera Reels Compact2, C40 and M40



RIDGID® SeeSnake® Compact series camera reels deliver big performance in a small package. Choose from three models to handle a wide range of demanding inspections. Compatible with the new SeeSnake CS6x Versa digital reporting monitor for fast set-up and easy viewing, while built-in Wi-Fi and Bluetooth make live streaming and inspection to an iOS™ or Android™ device simple with the free HQx Live app.

- 25 mm self-leveling camera head provides a crisp image that is always upright
- TruSense™ technology features two-way communication between the camera and a CSx series Wi-Fi enabled monitor*
- High dynamic range image sensor provides bright, saturated images with improved detail, even in difficult lighting conditions*
- TiltSense inclinometer lets you know camera's degree of tilt inside the pipe when used with a CSx series monitor*
- Equipped with high power FleXmitter® 512 Hz sonde which is compatible with all RIDGID locators
- Download the free HQx Live app to view and record inspection jobs on your phone or tablet
- Use with the SeeSnake CS6x Versa to create the optimal viewing angle and for fast, efficient job setup



* C40 and M40 camera reels only



SPECIFICATIONS

- Light Source High-Intensity LED
- Push Cable Length..... 100' (30 m)/131' (40 m)
- Push Cable Minimum Bend Radius.....2.5" (64 mm)
- 512 Hz Sonde High-power Flexmitter®
- Dimensions (LxWxH) 25" x 14" x 17"
(626 mm x 360 mm x 429 mm)
- Operating Temperature 14°F to 122°F (-10°C to 50°C)
- Storage Temperature..... 14°F to 158°F (-10°C to 70°C)
- Ingress Protection (without Monitor).....IPx6

COMPACT SERIES QUICK COMPARISON GUIDE

CAMERA REEL	CAMERA HEAD	PUSH CABLE	MINIMUM BEND RADIUS	LINE CAPACITY
Compact2 Camera Reel	25 mm (1") Self-Leveling	100' (30 m)	2.5" (64 mm)	1.5" - 6" (38 mm - 152 mm)
Compact C40 Camera Reel	 25 mm (1") Self-Leveling w/TruSense Technology	131' (40 m)	2.5" (64 mm)	1.5" - 6" (38 mm - 152 mm)
Compact M40 Camera Reel	 25 mm (1") Self-Leveling w/TruSense Technology	131' (40 m)	3" (76 mm)	1.5" - 8" (38 mm - 203 mm)

ORDER INFORMATION

CATALOG NO.	DESCRIPTION	WEIGHT	
		(lb.)	(kg)
48093	Compact2 (Reel Only)	17.0	7.7
65098	Compact2 w/CS6x Versa Monitor	21.9	9.9
65103	Compact2 w/CS6x Versa Monitor, Battery and Charger	24.9	11.3
63668	Compact C40 (Reel Only)	17.2	7.8
63823	Compact C40 w/CS6x Versa Monitor	22.1	10.0
63828	Compact C40 w/CS6x Versa Monitor, Battery and Charger	25.1	11.4
63673	Compact M40 (Reel Only)	22.0	9.8
63813	Compact M40 w/CS6x Versa Monitor	26.9	12.0
63818	Compact M40 w/CS6x Versa Monitor, Battery and Charger	29.9	13.6



HDR

High Dynamic Range (HDR) image sensor offers clear in-pipe imaging..



TiltSense™

Data Sensor displays camera's angle in pipe.



Scan for more information on HQx Live

ACCESSORIES

CATALOG NO.	DESCRIPTION
47793	36 mm Pipe Guide, 25 mm Camera, Pkg of 1
35338	45 mm Pipe Guide, 25 mm Camera, Pkg of 2
97462	60 mm Pipe Guide, 25 mm Camera, Pkg of 6
46708	85 mm Pipe Guide, 25 mm Camera, Pkg of 2
46713	125 mm Pipe Guide, 25 mm Camera, Pkg of 2
63868	Various Pipe Guides, 25 mm Camera Head
17553	Spanner Wrench, 25 mm



RIDGID.COM/seesnake

All sales subject to Ridge Tool Company Terms and Conditions of Sales. Catalog Sheet No. R-19-P (719) Effective Date: July 1, 2019
 ©2019 RIDGID, Inc. The Emerson logo and RIDGID logo are registered trademarks of Emerson Electric Co. or RIDGID, Inc. in the U.S. and other countries.
 All other trademarks belong to their respective holders.