

SPECIFICATIONS

FIGURE IS4CTHC - IS6CTHC

STAINLESS STEEL FITTINGS



304 & 316 STAINLESS STEEL THREADED HALF COUPLING

PRODUCT SPECIFICATIONS

- The material composition and quality requirements shall comply with ASTM A351/A351M
- Threads should be in accordance with ASME B1.20.1-1983



REFERENCE CHART (INCHES)

Item #	Size	L	A	B	Grade
IS4CTHCA	1/8	0.500	0.453	0.551	304
IS4CTHCC	3/8	0.563	0.748	0.846	304
IS4CTHCH	1-1/4	1.00	1.732	1.909	304
IS4CTHCK	2	1.252	2.402	2.622	304
IS4CTHCL	2-1/2	1.437	2.992	3.327	304
IS4CTHCM	3	1.591	3.602	3.957	304
IS4CTHCP	4	1.843	4.724	5.098	304
IS6CTHCA	1/8	0.500	0.453	0.551	316
IS6CTHCB	1/4	0.500	0.610	0.728	316
IS6CTHCC	3/8	0.563	0.748	0.846	316
IS6CTHCD	1/2	0.693	0.906	1.047	316
IS6CTHCF	3/4	0.752	1.102	1.252	316
IS6CTHCG	1	0.811	1.398	1.555	316
IS6CTHCH	1-1/4	1.00	1.732	1.909	316
IS6CTHCJ	1-1/2	1.063	1.988	2.165	316
IS6CTHCK	2	1.252	2.402	2.622	316
IS6CTHCM	3	1.591	3.602	3.957	316
IS6CTHCP	4	1.843	4.724	5.098	316

