

# SPECIFICATION SHEET 263-42202

# SECURE™ 2 PASSIVE EAR MUFFS -FULL BRIM MOUNTED NRR 24

- Fits most full brim hard hats on the market with universal slots
- Ear cups can be placed in three positions
- Slim profile design increases stability and reduces risk of snagging in confined spaces
- Smooth telescopic single-point size adjustment increases comfort, stability and wear time
- Soft and wide ear cushions feature snap-in system for easy replacement
- Dielectric, non-conductive
- Tested and CE approved against European, North American and Australian standards

### **APPLICATIONS**

- Medium to high noise levels, high frequency noise
- Food processing
- Industry
- Manufacturing
- Industrial work
- Auto mobile

### **TECHNICAL DATA**

MATERIAL	Ear Cups and Spacer: ABS thermoplastic Cushion: Polyether & PVC-foil Foam liner: Polyether Buckle and Arm: POM thermoplastic Spring Housing: POM thermoplastic 10% gf Screw for housing: Stainless steel Slot adaptor: PA 66 thermoplastic 10% gf Steel spring: Stainless spring steel
COLOR	Yellow / ■ Black
ATTENUATION	NRR: 24 dB / SNR: 29 dB
STYLE	Full Brim Mounted
SIZE	Adjustable
WEIGHT	9.6 oz / 271 g
PACKAGING	20 per case
CASE	22.05" x 13.78" x 11.81" / 56cm x 30cm x 35cm
CASE WEIGHT	17.63 lbs / 8 kg
C00	China

## **BARCODES**

ITEM	EACH	DOZEN	CASE			
263-42202	739144100176		739144100176			



### **ATTENUATION DATA**

FREQUENCY HZ	125	250	500	1000	2000	3150	4000	6300	8000	NRR	
Mean Attenuation dB	15.7	20.7	28.8	36.9	35.2	37.0	37.8	39.6	38.6	24	
Standard Deviation dB	2.8	2.1	3.0	2.9	3.2	3.4	2.2	2.4	2.8		

Tested in accordance with ANSI standard \$3.19-1974

Canada Class A (L)

FREQUENCY HZ	63	125	250	500	1000	2000	4000	8000	Н	M	L	SNR
Mean Attenuation dB	15,0	15,0	21,0	28,1	35,3	34,0	34,0	37,3		27	19	
Standard Deviation dB	4,1	2,6	3,1	3,5	4,0	3,8	4,5	4,4	31			29
APV dB	10,9	12,4	17,9	24,6	31,3	30,2	29,5	32,9				