### 30 205

### LADYLUX® L2



# SINGLE-HANDLE PULL DOWN KITCHEN FAUCET TRIPLE SPRAY WITH TOUCH TECHNOLOGY 1.75 GPM

#### STANDARD SPECIFICATION:

- GROHE SilkMove®
- GROHE StarLight®
- 16" Faucet height
- 8 9/16" Aerator height
- 9 3/16" Faucet reach
- · Touch activation of water via skin contact
- 6 V lithium-battery supply (type CR-P2)
- · CE approved and meets the requirements of IAPMO IGC 349-2017
- Automatic safety stop after 60 sec. (factory set)
- · Pull-down spray with 3 spray types: laminar spray, shower spray, and blade spray (reduced water consumption by up to 50% and even stronger spray performance)
- · Stop function pause button to stop the water flow
- Automatic return to laminar spray
- Adjustable flow rate limiter
- 360° Swivel spout
- Nylon braided flex hoses
- Quick installation system
- 1.75gpm



#### **PRODUCT FEATURES:**



GROHE SilkMove®



GROHE StarLight®



GROHE QuickFix®

#### **CERTIFICATIONS:**



- CEC Certified
- · Low Lead Certified
- CALGreen Compliant
- Massachusetts Plumbing Board Approved
- Energy Policy Act of 1992
- NSF 61
- CSA B125.1
- ASME A112.18.1
- · Complies with lead plumbing laws

#### **AVAILABLE FINISHES:**

30205002

GROHE StarLight® Chrome

30205DC2

SuperSteel InfinityFinish™

NOTE: Install this product according to the installation guide. ADA, CSA compliant when installed to the specific requirements of these regulations.



## LADYLUX® L2



# SINGLE-HANDLE PULL DOWN KITCHEN FAUCET TRIPLE SPRAY WITH TOUCH TECHNOLOGY 1.75 GPM

#### **TECHNICAL DATA:**

Product Height 14-15/16 in

Product Length 9-3/16 in

Product Width 6-1/4 in

Fitting Spout Height 8 in

Fitting Spout Reach 8-5/16 in

Fitting Handle Height 7-1/8 in

GPM (Min)-GPM (Max) 1.75 gal (US)/min

Fitting No of Holes Required 1

