



PFPTBVN SERIES PVC Threaded Ball Valves

Product Features

- Working Non-Shock Pressure (1/2" – 2"): 150 psi @ 73°F
- Working Non-Shock Pressure (2-1/2" – 4") 100 psi @ 73°F
- Media Temperature Range: 32°F – 140°F
- Valve Port Opening: 1/2" – 3" full port design; 4" regular port design
- Low flow loss
- Threaded end diameter conforms to ASTM D2464
- Certified to: NSF/ANSI 372, NSF/ANSI 14, NSF/ANSI/CAN 61




PFPTBVND

No.	Part	Material	Pieces
1	Body	UPVC	1
2	Ball	UPVC	1
3	Stem (Only for 3")	UPVC	1
4	Stem O-Ring	EPDM	1
5	Cap (Only for 1/2"-2")	ABS	1
6	Handle	ABS	1
7	Seat	EPDM	2
8	End Connector (Only for 3")	UPVC	1


Dimensions (inches)

Model No.	Nom. Size	D1	Threads (±1 turn)	L	D2	H	A
PFPTBVND	1/2	0.580	1/2" - 14 NPT	2.960	1.158	1.850	2.734
PFPTBVNF	3/4	0.780	3/4" - 14 NPT	3.248	1.429	2.152	3.000
PFPTBVNG	1	0.970	1" - 11.5 NPT	3.816	1.693	2.224	3.536
PFPTBVNH	1-1/4	1.250	1-1/4" - 11.5 NPT	4.325	2.039	2.461	3.527
PFPTBVNJ	1-1/2	1.510	1-1/2" - 11.5 NPT	4.831	2.408	2.865	4.398
PFPTBVNK	2	1.950	2" - 11.5 NPT	5.528	2.873	3.437	5.521
PFPTBVNL	2-1/2	2.550	2-1/2" - NPT	7.638	3.780	5.550	7.480
PFPTBVNM	3	3.050	3" - 8 NPT	9.173	4.331	6.063	9.005
PFPTBVNP	4	3.910	4" - 8 NPT	11.000	5.350	6.700	10.790

1/2"-2"



2-1/2-4"



Warranty and Codes

This PROFLO product carries a 1-year limited warranty.

