

## **MECHANICAL JOINT BLUE T-HEAD BOLT & GASKET PACKS**


## **Product Features**

T-Bolts/Nuts: Low-alloy steel in accordance with ANSI/AWWA C111/A21.11

- T-Bolts and nuts have fluoropolymer coating material, which is VOC-compliant, resin-bonded, thermally cured and dry lubricant
- Bolts and nuts are manufactured in accordance with ANSI/AWWA C111/A21.11
- Material is high-strength low-alloy steel per ANSI/AWWA C111/A21.11
- Threads per ASME B1.1 unified standard coarse (Class 2A & 2B)

Gaskets: SBR in accordance with ANSI/AWWA C111/A21.11

Property	ASTM Test Method	Required Value
Hardness, Shore "A"	D2240	75±5
Minimum Tensile	D412	1500psi
Minimum Elongation	D412	150%
Minimum Aging	D573	60%
Maximum Compression Set	D395, Method B	20%
Resistance to Surface Ozone Cracking	D1149	No Cracking



## **Product Specifications**

SKU	Size
PSMJBBGPP	4"
PSMJBBGPU	6"
PSMJBBGPX	8"
PSMJBBGP10	10"
PSMJBBGP12	12"
PSMJBBGP16	16"

PROSELECT Glands, Gaskets, T-head Bolts and Mechanical Joint Accessory Packs are sold exclusively through Ferguson Enterprises and its affiliates.

 $\label{thm:complex} \textit{Ferguson Enterprises guarantees the quality and compliance to the listed specifications}.$ 

PROSELECT is a registered trademark of Ferguson Enterprises.

## Warranty

• This PROSELECT product carries a 1-year limited warranty.