



#### **Product Features**

- Pressure compensating for constant flow from 20 to 80 psi.
- Construction inhibits lime build up.
- Anti-clogging dome screen filters sediment and particles.
- Compatible with all regular male and female housings.
- · Rubber washer.




PF143129PK

#### **Model Numbers**

PF5061CPK PF143129PK PF143163 \*PF143173



# **Product Specifications**



#### **PROFLO Aerators**

ITEM	DESCRIPTION	GPM(LPM)
PF5061CPK	Dual Thread. 15/16" (23.8mm) -27 TPI Male X 55/64" (21.8mm) -27 TPI Female CP 12 Pack	2.0 (7.58)
PF143129PK	Female. 55/64" (21.8mm) -27 TPI. CP	1.5 (5.685)
PF143163	Female. 55/64" (21.8mm) -27 TPI. CP	0.5 (1.89)
PF143173	Male. 15/16" (23.8mm) -27 TPI. CP	1.0 (3.79)

### **DIMENSIONS**

	Α		В		C	
ITEM	IN	MM	IN	MM	IN	MM
PF5061CPK	15/16	23.8	13/16	20.6	13/16	20.6
PF143129PK	15/16	23.8	13/16	20.6	5/8	15.8
PF143163	29/32	23.0	7/8	22.2	11/16	17.4
PF143173	15/16	23.8	7/8	22.2	1/2	12.7

## Warranty and Codes

Meet ANSI/NSF 61, ASME A112.18.1M, CS B125 requirements. This PROFLO product carries a 1-year limited warranty. \*WaterSense Listed