

America's Finest Penetrating Oil

PRODUCT DESCRIPTION:

America's Finest Penetrating Oil is a premium quality penetrating oil, compounded for professionals, mechanics and engineers. It is formulated with a proprietary blend of the finest available oils, the most effective wetting agents, and Moly to meet the toughest industrial standards.

PRODUCT BENEFITS:

America's Finest Penetrating Oil has a powerful high-performance solvent that quickly cuts through rust, dirt, grease and corrosion, penetrating the smallest cracks, while the molybdenum disulfide is drawn in for easy separation and long-lasting lubrication.

APPLICATION:

America's Finest Penetrating Oil frees and lubricates:

- Rusted nuts and bolts
- Manifold heat valves (heat risers)
- Valves, stems, rocker arms, hydraulic lifters
- Tie rod knuckles, mufflers and tailpipes
- Door hinges, door locks, hood hinges

Additional uses include:

- Removes rubber squeaks from shock absorbers, motor mounts, etc.
- Prevents sticking of fast idle cams and automatic chokes due to gumming
- Leaves a residual protecting film of molybdenum disulfide

TECHNICAL DATA:

Propellant:	Propane and n-Butane
Flash Point:	320°F (160°C) Oil, typical
Spray Pattern:	Narrow Stream
Texture:	Light Oil with Fine MOS ₂ Particulate
Appearance:	Gray
Consistency:	Light
Specific Gravity:	0.87 for Concentrate, typical

AEROSOL PACKAGING:

11 oz. net weight aerosol cans (12/case) — Part # JAX101

BULK PACKAGING:

Trigger spray bottles (16 fl. oz., 12/case), Gallons (4/case), 5-Gal pails and 55-Gal drums — Part # 00101



America's Finest Penetrating Oil



NSF International / Nonfood Compounds Registration Program

May 19, 2004

Patty Riek
PRESSURE-LUBE, INC. JAX
W134 N5373 CAMPBELL DRIVE
MENOMONEE FALLS, WI 53051
UNITED STATES

RE JAX AMERICA'S FINEST PENETRATING OIL (Aerosol)
Category Code: H2
NSF Registration No. 133888

Dear Patty Riek:

NSF has processed the application for Registration of **JAX AMERICA'S FINEST PENETRATING OIL (Aerosol)** to the *NSF Registration Guidelines for Proprietary Substances and Nonfood Compounds (2004)*, which are available at www.nsf.org. The NSF Nonfood Compounds Registration Program is a continuation of the USDA product approval and listing program, which is based on meeting regulatory requirements including FDA 21 CFR for appropriate use, ingredient and labeling.

This product is acceptable as a lubricant where there is no possibility of food contact (H2) in and around food processing areas. Such compounds may be used as lubricants, release agents, or antirust films on equipment and machine parts in locations in which there is no possibility of the lubricant or lubricated part contacting edible products.

NSF Registration of this product is current when the NSF Registration Number, Category Code, and Registration Mark appear on the NSF-approved product label, and the registered product name is included in the current NSF White Book Listing of Nonfood Compounds at the NSF website (<http://www.nsf.org>). The NSF Registration Mark can be downloaded from the NSF website, at http://www.nsf.org/business/about_NSF/nsf_marks_download.asp.

NSF Listing of all registered Nonfood compounds by NSF International is not an endorsement of those compounds, or of any performance or efficacy claims made by the manufacturer.

Registration status may be verified at any time via the NSF web site, at <http://www.nsf.org>. Changes in formulation or label, without the prior written consent of NSF, will void registration, and will supersede the on-line listing.

Sincerely,

Carmen Grindatti
NSF Nonfood Compounds Registration Program

Company No: N05625

Distributed By:

PRESSURE-LUBE
America's Finest Lubricants

W134 N5373 Campbell Drive • Menomonee Falls, WI 53051
262.781.8850 • 800.782.8850 • FAX 262.781.3906
www.jax.com