


MOTOR FINISH

 Brushed Nickel

BLADE FINISHES

Brushed Nickel

 Dimmable

 LED Light Kit



AIR PERFORMANCE

AIRFLOW Cubic Ft. Per Minute on High	RPM Revolutions Per Minute on High	POWER USAGE Watts on High (Excludes Lights)	AIRFLOW EFFICIENCY Cubic Ft. Per Minute Per Watt
5620	137	73	87

CFM (Low)	2029
RPM (Low)	58
Watts (Low)	15

SPECIFICATIONS

Light Source			
Dimmable	Yes	Downlight Included	Yes
Downlight Option	Integrated	Lamp Included	Integrated
Light Source	LED	# of Bulbs/LED Modules	1
Watts (High)	73	Watts (Low)	15
Photometrics			
Color Rendering Index	90	Delivered Efficacy (Lumens/Watt)	80
Kelvin Temperature	3000K		
Electrical			
Amps (High)	0.61	Amps (Low)	0.28
Motor Size	172MM X 20MM	Motor Type	AC
Supply Wire (Degrees)	90		
Dimensions			
Base Backplate	6.75 DIA	Downrod 1	1.00" OD X 6.00"
Downrod 1 - Measurement A	14.75"	Downrod 1 - Measurement B	10.50"
Downrod 1 - Measurement C	10.50"	Weight	23.80 LBS
Mounting/Installation			
Minimum Distance from Fan to Floor	7.0 feet	Interior/Exterior	Interior
Lead Wire Length	78"	Location Rating	Dry
Low Ceiling Adaptable	No	Mounting Style	Downrod
Mounting Weight	18.30 LBS		

FIXTURE ATTRIBUTES

Product/Ordering Information			
SKU	330089NI	Finish	Brushed Nickel
Style	Transitional	UPC	783927604024

Housing

Diffuser Description	Frosted White Polycarbonate	Primary Material	STEEL
Max Stem Tilt	18 Degrees	Remote Included	Yes

Blade Finish & Specs

Blade Finish 1	BRUSHED NICKEL	Blade Material	ABS
Blade Pitch	12	Blades Included	Yes
Blade Sweep	52	Number of Blades	5

Warranty

www.kichler.com/warranty

ALSO IN THIS FAMILY



330089SBK



330089WH

You can see all products in this family by searching Kichler.com