

Protector+ Filter Fluid 500ml

62436

- Protects against corrosion and scale in mixed metal central heating systems to prevent breakdown and premature boiler failure
- Quick and convenient – doses in 30 seconds via radiator, filling loop or Fernox TF1 System Filter - no need to drain down the system
- When used in conjunction with Cleaner F3 gas savings of up to 15% can be achieved every time you heat your room
- Supports boiler manufacturer's warranty requirements
- One 1 pint recyclable bottle treats up to 34 gallons of system water (16 radiators)
- High performance, non toxic, environmentally friendly - NSF, KIWA and Belgaqua approved formulation



Protector F1 is the market leading inhibitor which prevents corrosion and limescale formation in central heating systems. This high performance product offers superior protection by uniquely combining three inhibitors of organic particles, which bind to the metal within the heating system to protect from debris alongside anodic inhibitors which react with the system's metal surface to create a protective layer, and cathodic inhibitors that combine with hard water salts to form an insoluble layer. Fernox Protector F1 also includes enhanced a pH buffering to ensure the system water pH level does not drop below 6.5 or above 8.5 - the optimum pH range for preventing corrosion and limescale buildup. In line with local regulations and best practice, and for long-term protection of the system, concentration levels should be maintained and checked annually as part of the boiler or system service. Protector F1 is compatible with all other Fernox products and is suitable for use with all materials and metals used in central heating systems, including Aluminum. The Fernox Express range uses Barrier Pressure Pack technology and compressed air propellant to expel the product so the entire range is non-flammable. The propellant (compressed air) is not mixed with the active product so there is no risk of air ingress into the system which could accelerate future risk of corrosion.

Single Item

Height mm	218
Width mm	66
Depth mm	95
Weight kg	0.600
Barcode EAN	5014551624368

Outer Carton

Outer Height mm	241
Outer Width mm	178
Outer Depth mm	339
Outer Weight kg	6.240
OCU Barcode	5.01455E+12
Transit Type	Euro 1200 x 800
Units per carton	10
Cartons per layer	12
Total units per transit layer	120
Layers per transit type	5
Total units per transit type	600

Last modification 21-04-2021 (d/m/y)