

ITEM # RK30NMVJUA, 0.75-TON WALL MOUNTED UNIT

MINI SPLIT OD-BML AC



[Specifications](#) | [System Efficiency Metrics](#) | [Dimensions](#)

Specifications

Cooling Capacity	31400 Btu/h
Min Cooling Capacity	10200 Btu/h
Max Cooling Capacity	31400 Btu/h
Running Current (Rated)	14.2 to 15.7 A
Power Consumption Rated	3188 W
Min Power Consumption	610 W
Max Power Consumption	3188 W
Power Factor	97.6 %
Heat Insulation	Both Liquid and Gas Pipes
Amount of Additional Charge of Refrigerant	0.32 oz/ft 30 g/m
Casing Color	Ivory White
Compressor Type	Hermetically Sealed Swing Type
Compressor Model	2YC63AAXD
Compressor Motor Output	1920 W

Refrigerant Oil Type	FVC50K
Refrigerant Oil Charge	0.900 L
Refrigerant Type	R-410A
Refrigerant Charge	3.64 lb 1.65 kg
Airflow Rate (H)	2528 ft ³ /min 71.6 m ³ /min
Fan Type	Propeller
Fan Running Current (Rated)	13.50 to 14.93 A
Fan Power Consumption Rated	3098 W
Fan Power Factor (Rated)	99.8 %
Sound Pressure Level	56 dBA
Weight	133 lb 60 kg
Gross Weight	142 lb 64 kg

System Efficiency Metrics

System Performance SEER	17.5
System Performance EER	9.85 Btu/h·W

Dimensions

Depth	12-5/8 in 320 mm
Width	34-1/4 in 870 mm
Height	28-15/16 in 735 mm

Pipe Connections - Liquid	1/4 in 6.4 mm
Pipe Connections - Gas	5/8 in 15.9 mm
Pipe Connections - Drain	5/8 in 16.0 mm
Max. Interunit Piping Length	98-3/8 ft 30 m
Max. Interunit Height Difference	65-5/8 ft 20 m
Chargeless	32-13/16 ft 10 m