

PRESSURE BALANCING SHOWER HEAD, HANDSPRAY, SHOWER HEAD/SHOWER HEAD VALVE BODY SPECIFICATION SUBMITTAL

S262XBODY

S162XBODY

MODEL NUMBERS

☐ S262XBODY

Pressure Balancing tub/shower valve body with integral diverter and service stops

☐ S162XBODY

Pressure Balancing tub/shower valve body with pressure testing cap, integral diverter and service stops

FEATURE HIGHLIGHTS

- Brass, bronze and stainless steel construction
- Pressure balancing mixing valve to maintain safe shower temperature
- Integral diverter control
- Adjustable stop screw to control maximum hot water temperature to valve
- Integral service stops allow water shut-off for valve servicing
- 4 port valve body in common plane
- Inlets: 1/2" IPS and 1/2" sweat
- Outlets: 1/2" IPS and 1/2" sweat
- Accommodates back to back installations
- Accommodates thin wall installations
- Stringer mounts included
- Includes Versaflex diverter. Outlets not to be plugged.

OPTIONS/MODIFICATIONS

-BR	Temptrol Rapid Install™ Bracket
-CHKS	Integral check stops for use in installations where a positive shut-off device is used
-RV	downstream of valve Reverse seat for back to back installations
-NS	Name also weed alive where

Non-shared diverter

INLET ADAPTERS

- ☐ -CP CPVC fittings
 ☐ -P1 PEX crimp fittings
- ☐ -P2 PEX expansion fittings

ProPress fittings

- ASME A112.18.1/CSA B125.1
- ASSE 1016

COMPLIANCE

-P3

• Buy American Act Compliant ©







