SPECIFICATIONS

FNW7896 REFRIGERANT LINES SUPPORT

THREADED ROD HANGER SYSTEM

The TRH Hanger System provides a superior fit and finish to better meet contractor and engineer specifications. Simply squeeze the tips together and the spring steel hanger can be secured or adjusted in seconds.

FEATURES

- The TRH Hanger System supports a pair of insulated flow and return refrigerant lines on 1/4" to 3/8" threaded rod.
- Simply fold the lock-tab over to secure the lines into the strap.
- The spring steel hanger grips the rod tightly, and the black zinc coating offers corrosion resistance while matching the insulation color.
- The clamp can be detached from the rod hanger and used to secure lines to flat surfaces.



Catalog No.	Part No.	Threaded Rod Diameter	А	В	С
FNW7896K	TRH-2 (Pack of 10)	1/4" — 3/8"	1.28"	3.12"	3.82"
FNW7896M	TRH-3 (Pack of 10)	1/4" - 3/8"	1.40"	3.28"	3.70"
FNW7896P	TRH-4 (Pack of 10)	1/4" - 3/8"	2.40"	4.17"	5.00"
FNW7896S	TRH-5 (Pack of 5)	1/4" - 3/8"	3.38"	6.26"	7.03"



