



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S39062 - 11.6 watt LED Direct Wire Downlight; Edge-lit; 5-6 inch; 3000K; 120 volt; Dimmable

- Air Tight
- IC Rated



ELECTRICAL

Technology:	LED
Watts:	11.6W
Volts:	120V
Lumens:	730L
CRI:	90
CCT (Kelvins):	3000K
Temperature:	Warm White
Beam Spread :	100
Hours Rated:	40000
Dimmable:	Yes-Dimmable
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable
Incandescent Equivalent :	65W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Replaceable Light Source :	No
Number of LEDs :	54
Connection:	Direct Wired
Power Factor :	0.97
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923390623
Each Quantity:	1
Each Dimensions:	2.64 x 8.46 x 7.09
Case UPC:	10045923390620
Case Quantity:	12
Case Dimensions:	18.11 x 15.16 x 9.06

PHYSICAL

Finish:	White
Lens Finish:	Frost
Lens Material:	Plastic (PS)
Finish Family:	White
Dimensions:	H:1.94" DIA:7.13"
Weight (Lbs.):	0.6
Material:	Thermal Conductive Plastics

INSTALLATION

Ceiling Aperture:	6.4375 in. Cutout
Max Drywall Thickness:	3/4 in.
Clearance Height:	2.36

COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	ESID-2382154
Energy Star Lamp Category:	Downlight Recessed
CA Prop 65:	Lead
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

ACCESSORIES



80-947 6" Goof Ring for Remote Driver Installation



80-952 Rough-In Mounting Plate; 6" with Junction Box

DIMMER COMPATIBILITY

Leviton 6672

Leviton 6674

Satco 86/103

Lutron CTRP-253P

Eaton DALo6P-C2

Leviton DSLo6-1LZ

Lutron DVRP-253P

Leviton DW6HD

Leviton IPEo4-1L

Leviton IPLo6

Lutron MA-PRO

Lutron NTCL-250

Lutron NTRP-250

Legrand RH7o3PTUTC

Eaton SALo6P

Eaton SUF7

Eaton TALo6P-C2
