



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S39056 - 8.5 watt LED Direct Wire Downlight; Edge-lit; 4 inch; 3000K; 120 volt; Dimmable

- Air Tight
- IC Rated



ELECTRICAL

Technology:	LED
Watts:	8.5W
Volts:	120V
Lumens:	500L
CRI:	90
CCT (Kelvins):	3000K
Temperature:	Warm White
Beam Spread :	100
Hours Rated:	40000
Dimmable:	Yes-Dimmable
Dimmable Down To %:	100 to 20 percent
Dimming Type :	Forward Phase or Reverse Phase or Phase Selectable or Triac
Incandescent Equivalent :	45W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Replaceable Light Source :	No
Number of LEDs :	42
Connection:	Direct Wired
Power Factor :	0.93
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923390562
Each Quantity:	1
Each Dimensions:	2.56 x 6.30 x 5.12
Case UPC:	10045923390569
Case Quantity:	12
Case Dimensions:	13.58 x 11.02 x 9.06

PHYSICAL

Finish:	White
Lens Finish:	Frost
Lens Material:	Plastic (PS)
Finish Family:	White
Dimensions:	H:1.94" DIA:5.00"
Weight (Lbs.):	0.4
Material:	Thermal Conductive Plastics

INSTALLATION

Ceiling Aperture:	4.3125 in. Cutout
Max Drywall Thickness:	3/4 in.
Clearance Height:	2.36

COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	ESID-2382153
Energy Star Lamp Category:	Downlight Recessed
CA Prop 65:	Lead
FCC Compliant:	Yes
RoHS Compliant:	Yes
Restrictions:	No Restrictions

ACCESSORIES



80-950

Rough-In Mounting Plate; 4" with Junction Box

DIMMER COMPATIBILITY

Leviton	6674
Leviton	66ELV
Satco	86/103
Legrand	ADTP703TU
Lutron	CTRP-253P
Eaton	DALo6P-C2
Lutron	DVLV-600P
Lutron	DVRP-253P
Leviton	DW6HD
Leviton	IPE04-1L
Leviton	IPL06
Lutron	MA-PRO
Lutron	NTCL-250
Lutron	NTRP-250
Legrand	RH703PTUTC
Satco	S11268
Eaton	SALo6P
Lutron	SLV-600P
Eaton	SUF7