














PART NO. 025200

200 PIECE O-RING KIT



- Packed in resealable plastic case with fitting chart on lid
- Manufactured from nitrile compound

 NO. 010 - 35 PIECES	 NO. 012 - 25 PIECES	 NO. 111 - 15 PIECES	 NO. 113 - 10 PIECES	 NO. 115 - 10 PIECES	 NO. 211 - 8 PIECES
 NO. 011 - 35 PIECES	 NO. 110 - 25 PIECES	 NO. 112 - 10 PIECES	 NO. 114 - 10 PIECES	 NO. 116 - 10 PIECES	 NO. 212 - 7 PIECES



Durometer: 70°

Temperature Range:
22°F to ~212°F

NO.	ID -AS568 (inch)	Measured (inch)	CS (W.) -AS568 (inch)	Measured (inch)
212	0.859±0.010	0.858	0.139±0.004	0.138
211	0.796±0.010	0.795	0.139 ±0.004	0.138
116	0.737± 0.009	0.740	0.103± 0.003	0.106
115	0.674± 0.009	0.676	0.103± 0.003	0.101
114	0.612+0.009	0.613	0.103+0.003	0.102
113	0.549±0.007	0.551	0.103± 0.003	0.102
112	0.487± 0.005	0.491	0.103± 0.003	0.102
111	0.424± 0.005	0.425	0.103± 0.003	0.101
110	0.362± 0.005	0.361	0.103± 0.003	0.102
012	0.364± 0.005	0.366	0.070± 0.003	0.068
011	0.301+0.005	0.304	0.070+0.003	0.068
010	0.239± 0.005	0.240	0.070± 0.003	0.070

Dimensions of O-rings meet AS568 standard.