



Metro Fixed Rail MTRF Series

Features

This decorative dimmable fixed rail features reliable high-performance LEDs. Heads swivel and pivot to direct light where needed. Applications that this fixture could fit well include: kitchens, retail environments, and anywhere that needs highlighted illumination. The fixture mounts to a standard junction box (not included). These fixtures mount to the ceiling or wall.

Construction

The canopy is 22-gauge stamped steel and the rail is made of 20-gauge steel tube. Power supply connections must be made inside a junction box (not included).

Finish

The canopy, rail, and individual rail heads are plated in a satin nickel finish with a clear lacquer topcoat.

Diffuser

Frosted clear glass.

Electrical

Input 120 VAC/60 Hz. Dimmable with standard 2-wire (TRIAC) or electronic low voltage (ELV) dimmer switch.

LED

Fixture is supplied with integrated LED rail heads. Each rail head contains non-replaceable high power LEDs which produce a total of 450 lumens/head. The LEDs have an average life of 50,000 hours. 3000K. 90 CRI.

Certification

All fixtures are cETLus listed for indoor damp locations.
ENERGY STAR® qualified
Title 24/JA8 Compliant

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions
subject to change without notice.

Ordering Information:

Satin Nickel	LED	Source Lumens	L	W	H
MTRF4450L30SN	25W	1800	36-5/8"	5-15/16"	6-13/16"

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

