



PVC Swing Check Valve Features:

- No metallic parts, corrosion resistant..
- Full flow design.
- Angle seat and weighted flapper designed for low pressure seal.
- PVC weighted and shielded flapper will retain backpressure up to 125 psi.
- Iron pipe sized 1/2" - 4".
- Compression style for IPS sized plastic or metal pipe 1 1/4" - 3"
- Ideal for close working areas, easy pipe alignment.
- Compression ends can be used as union connections.
- Designed for both horizontal and vertical use.
- Pressure rated 125 psi @ 72°F.
- NSF/ANSI 61+372.



1500 Series

NSF/ANSI
61+372

Part Number	IPS Size	Body Length	Ctn Qty
PVC Swing Check Valve - WHITE comp x comp			
1500-12	1-1/4"	7-1/2"	12
1500-15	1-1/2"	7-1/2"	12
1500-20	2"	9-3/4"	12
1500-30	3"	14"	2

PVC Swing Check Valve - CLEAR comp x comp			
1500C-15	1-1/2"	7-1/2"	5
1500C-20	2"	9-3/4"	8

1520 Series

NSF/ANSI
61+372

PVC Swing Check Valve - WHITE slip x slip			
1520-05	1/2"	4-1/2"	25
1520-07	3/4"	4-1/2"	25
1520-10	1"	5-1/8"	25
1520-12	1-1/4"	5-1/4"	12
1520-15	1-1/2"	5-3/4"	12
1520-20	2"	6"	12
1520-30	3"	9"	4
1520-40	4"	9-1/2"	4



1520C Series

NSF/ANSI
61+372

PVC Swing Check Valve - CLEAR slip x slip			
1520C-10	1"	5-1/8"	1
1520C-12	1-1/4"	5 1/4"	1
1520C-15	1-1/2"	5 3/4"	12
1520C-20	2"	6"	12



1720 Series

NSF/ANSI
61+372

True Union Swing Check Valves - WHITE slip x slip			
1720-15	1 1/2"		12
1720-20	2"		12



1720C Series

NSF/ANSI
61+372

True Union Swing Check Valves - CLEAR BODY, WHITE NUTS/TAILS slip x slip			
1720C-10	1"		20
1720C-15	1 1/2"		12
1720C-20	2"		12
1720C-30	3"		20