LIFT-ALL HOIST BASICS

Lift-All hoists are perfect for a low-headroom lift. These economical, durable, and lightweight hoists are excellent options for a variety of lifting applications.

- The fully enclosed gears are protected from contamination.
- Powder-coated and plated finishes on exposed components protect the hoists from corrosion.
- All gears and shafts run on caged roller bearings for smooth operation and long life (excludes mini pullers).
- The self-adjusting Weston style mechanical load brake never requires adjustment.
- The top hook mounting aids in rigging and helps ensure straight line loading between hooks.
- All Lift-All hoists meet ASME B30, OSHA 1915.114, and NASA-STD-8719.9.




MANUAL CHAIN HOIST (MCH)

Maintains all the basic hoist features plus...

- Hand chain opening allows operation from side or above permitting use for both lifting or pulling.
- Internal parts are heat treated for strength and reliability with fully enclosed gearing to protect from contamination.
- Precision hoist load chain with strength of G80 chain.
- Weston style mechanical load brake is self-adjusting with double pawls, asbestosfree brake discs and is surrounded by an enclosure to limit contamination.

Part Number	Lift (ft.)	*WLL (Metric Tons)	Load Chain (lbs./ft.)	Hand Chain (lbs./ft.)	Dimensions (in.)				P Effort	Wgt.
					A min.	В	С	D	lbs. @ WLL	10' Lift (lbs.)
MCH005X10	10	0.5	0.54	0.38	10.6	5.4	5.4	1.10	45	22
MCH005X20	20									
MCH005X30	30									
MCH010X10	10	1	0.54	0.38	13.4	6.4	5.8	1.02	72	26
MCH010X20	20									
MCH010X30	30									
MCH015X10	10	1.5	0.92	0.38	15.7	7.2	6.7	1.28	81	42
MCH015X20	20									
MCH015X30	30									
MCH020X10	10	2	0.92	0.38	16.3	7.6	6.7	1.26	82	44
MCH020X20	20									
MCH020X30	30									
MCH030X10	10	3	1.84	0.38	20.9	8.7	6.7	1.46	87	59
MCH030X20	20									
MCH030X30	30									
MCH050X10	10	5	2.96	0.38	25.0	11.3	7.5	1.80	98	101
MCH050X20	20									
MCH050X30	30									
MCH100X10	10	10	5.92	0.38	29.3	15.1	7.5	1.97	98	183
MCH100X20	20									
MCH100X30	30									







[•] Do not exceed working load limit (load rating capacity).

Read and follow all instructions.Do not use to lift people.

Use only alloy chain for overhead lifting.

Do not lift loads over people.