

Location: _____



MI-QXHUB

HEAVY DUTY QUICK HUB NO HUB COUPLINGS

Specification: MIFAB® Series MI-QXHUB (specify size) heavy duty shielded no hub couplings are manufactured with gaskets made from neoprene and three sealing rings (meets the requirements of ASTM C564) housed inside a Type 304 stainless steel corrugated shield. Four (2" through 4" size), six (5" through 12" size) Type 304 stainless steel clamps tightened with 3/8" Type 305 stainless steel hex head screws surround the shield to provide the sealing force. MI-QXHUB Series Couplings are tested and certified to the ASTM-C1540 and CSA B602 Standards. The MI-QXHUB are also tested and certified by Intertek Testing Services to the CAN/ULC S102.2 "Smoke Test". The MI-QXHUB are tested and certified by IAPMO to comply to the FM1680 Standard (except for markings). Patented Pipe Clamp for joining all types of pipe.

Function: Used to provide a positive and significant seal between no hub cast iron pipe and fittings. The patented sealing rings within the Quick Hub gasket ensure that the gasket remains within the shield during shipping and handling and also a quick push on installation onto the pipe. There is no need to remove the gasket first and roll it over the pipe. With Quick Hub, you simply push the coupling onto the pipe.

Material Specifications:

Bands: Type 304 AISI stainless steel (Minimum tensile 165,000 psi).

Eyelets: Type 304 AISI stainless steel.


Gasket: Neoperene - meets the requirements of ASTM C564.

Oil Immersion Test: 80% max. Volume change after immersion in IRM 903 for 70 hours at 212° F.

Screw Housing - Type 304 AISI Stainless steel.

Eyelets - Type 305 AISI stainless steel, 3/8" Hex head/shoulder.

Shield - Type 304 AISI stainless steel painted red for easy identification.



The MI-QXHUB Quick Hub couplings are also tested and certified to the ASTM C1460 Standard to connect cast iron pipe to PVC and / or ABS pipe in the 1 1/2", 2", 3", 4", 6" and 8" size range.

Patent #
10,557,578

Patent #
10,253,885

Patent #
10,100,956

"A quality coupling, easy to install, and definitely a time-saver."

- Forest Powell, General Foreman Collins Plumbing, Southern California

MI-QXHUB:

Three sealing rings on the MI-QXHUB gaskets outperform others with only two sealing rings.

Sizes 5" through 12"
 Tighten inside bands first, then outside bands.

Sizes 2" through 4"
 Tighten inside bands first, then outside bands.

MODEL NUMBER	PIPE SIZE (NOMINAL DIA.)	(C) HEIGHT	INSTALLATION TORQUE (IN. - LBS)	ASTM C1540 HYDROSTATIC PRESSURE REQUIREMENT	NUMBER OF CLAMPS PER COUPLING	BAND WIDTH (CLAMP)
MI-QXHUB-150	1 1/2"	3"	80-100	30 psi	4	9/16"
MI-QXHUB-2	2"	3"	80-100	30 psi	4	9/16"
MI-QXHUB-3	3"	3"	80-100	30 psi	4	29/64"
MI-QXHUB-4	4"	3"	80-100	30 psi	4	9/16"
MI-QXHUB-5	5"	4"	80-100	30 psi	6	9/16"
MI-QXHUB-6	6"	4"	80-100	27 psi	6	9/16"
MI-QXHUB-8	8"	4"	80-100	15 psi	6	9/16"
MI-QXHUB-10	10"	4"	80-100	9 psi	6	9/16"
MI-QXHUB-12	12"	5.43"	80-100	6 psi	6	5/8"

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

Job Name: _____	Page No: _____
Section No: _____	Contractor: _____
Schedule No: _____	Purchase Order No: _____