SPEC

PFWSC3840

BOTHWELL TWO HANDLE LAVATORY FAUCET

Product Features

- Max. flow rate: 1.2 gpm at 60 psi
- · Metal handles
- Ceramic disc cartridges
- With 50/50 pop-up
- Requires 3-Holes Sink With 4" On-Center •
- Certified to ASME A112.18.1 / CSA B125.1 •
- cUPC/IAPMO listed
- ADA compliant
- NSF/ANSI/CAN61: Q≤1 •
- WaterSense certified



(PROFLO_®

PFWSC3840CP

5 1/2" [139.5mm]

Model Numbers

PFWSC3840CP	Chrome
PFWSC3840ZBN	Brushed nickel
PFWSC38400RB	Oil rubbed bronze

9 1/4" 3 3/4" [95.1mm] [234.7mm] 146.5mm] 5 3/4" 4 1/4" 107.3mm] 2 3/8" 1/2"-14NPSM-2A [61.0mm] ᆍ 7 ⊒⊫ [29.2mm] 1 1/8" M 3/8" 9.91mm] 2 1/8" [53.98mm] [101.6mm] 1 1/2"-18UNEF 1 5/8" -2 7/16" [41.18mm]-[61.53mm] [221.70mm] 8 3/4"

Warranty and Codes

This product comes complete with installation, operating, care and maintenance instructions.

This PROFLO faucet carries a limited lifetime warranty when installed in residential applications.

The warranty is five years in commercial applications.

*Compliant with lead content requirements of California AB 1953.

Distributed Exclusively by Ferguson and Wolseley Canada ©2022 Ferguson Enterprises, Inc. All Rights Reserved



1 1/4"

[32.00mm]

FERGUSON.COM/PROFLO

06/06/22 Rev.B