

Heliopex X2

Project information

|                                |                 |
|--------------------------------|-----------------|
| Job name:                      | Location:       |
| Engineer:                      | Date submitted: |
| Contractor:                    | Submitted by:   |
| Manufacturer's representative: | Approved by:    |

Technical data

|                       |                                     |
|-----------------------|-------------------------------------|
| Material              | PEX                                 |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar)   |
|                       | 180 °F (82 °C) at 100 psi (6.9 bar) |
|                       | 200 °F (93 °C) at 80 psi (5.5 bar)  |

Product information and application use

Uponor helioPEX X2 is Uponor's new oxygen-barrier PEX pipe manufactured using an Uponor proprietary technology, proving a competitive alternative to other closed-loop radiant heating tubing products in the market. Key differentiators between Uponor helioPEX X2 and Wirsbo hePEX include, select diameters and coil lengths, not for potable applications and a 25-year limited warranty. Uponor helioPEX X2 is rated and listed by the Hydrostatic Stress Board of PPI at 200°F (93.3°C) at 80 psi, 180°F (82.2°C) at 100 psi and 73.4°F (23°C) at 160 psi and features an oxygen barrier that conforms to DIN 4726. The tubing is compatible with Uponor ProPEX and QS-style fittings and is manufactured in full compliance to ASTM F876 (including dimensional requirements for barrier tubing), ASTM F877 and CSA B137.5.



| Part name                               | Part no. | Inner diameter coil [inch] | Outer diameter coil [inch] | Coil width [inch] | Inner diameter pipe [inch] | Outer diameter pipe [inch] | Weight per UOM [lbs/UOM] |
|-----------------------------------------|----------|----------------------------|----------------------------|-------------------|----------------------------|----------------------------|--------------------------|
| 5/8" Uponor helioPEX X2, 400-ft. coil   | H1210625 | 15.75                      | 32                         | 6.5               | 0.574                      | 0.75                       | 35                       |
| 1/2" Uponor helioPEX X2, 1,000-ft. coil | H1220500 | 15.75                      | 32                         | 10.5              | 0.475                      | 0.625                      | 57.5                     |
| 5/8" Uponor helioPEX X2, 1,000-ft. coil | H1220625 | 15.75                      | 32                         | 16                | 0.574                      | 0.75                       | 86                       |
| 1/2" Uponor helioPEX X2, 500-ft. coil   | H1240500 | 15.75                      | 32                         | 6.5               | 0.475                      | 0.625                      | 28.75                    |
| 3/4" Uponor helioPEX X2, 500-ft. coil   | H1240750 | 15.75                      | 32                         | 10.5              | 0.671                      | 0.875                      | 56.5                     |
| 1/2" Uponor helioPEX X2, 300-ft. coil   | H1250500 | 19.7                       | 32                         | 4                 | 0.475                      | 0.625                      | 16.53                    |
| 3/4" Uponor helioPEX X2, 300-ft. coil   | H1250750 | 22                         | 32                         | 8                 | 0.671                      | 0.875                      | 30.2                     |

| Installation | Related applications |
|--------------|----------------------|
|--------------|----------------------|

Approved fitting system is ProPEX®. Refer to the Uponor Radiant Floor Heating Installation Handbook for further information.

-

| Codes                                | Standards                                                                                       | Listings                                                         |
|--------------------------------------|-------------------------------------------------------------------------------------------------|------------------------------------------------------------------|
| IRC NBC of Canada UFGS UMC USEHC IMC | ASTM F877 ASTM E814 ULC S115 ASTM F1960 ULC S102.2 CSA B137.5 CSA B214 ULC S101 ASTM E84 NSF-14 | cNSFus-rfh CCMC PPI TR-4 ASTM E84 ULC S102.2 UL 2846 cQAIus P321 |

| Footnotes | Contact information                                                                                                                                                                                                               |
|-----------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| -         | <div>Uponor Inc.<br/>5925 148th Street West<br/>Apple Valley, MN 55124<br/>T 800.321.4739<br/>F 952.891.2008</div> <div>Uponor Ltd.<br/>6510 Kennedy Road<br/>Mississauga, ON L5T 2X4<br/>T 888.594.7726<br/>F 800.638.9517</div> |