



Cover All You Need for Opening

Alfa Laval Access Tank Cover - Oval Type O

Application

The Type O stainless steel manhole covers are used on tanks and containers used in a wide range of sanitary applications such as wine, beverages, dairy and foodstuffs. They are designed to fit where a closeable mean of access to the interior of the vessel, situated below the liquid level, is required.

Working principle

Open the cover by loosening the handle. This range includes covers with various openings. For inspection purposes there are covers with inwards opening. If it is necessary to physically enter the tank there are covers with outwards and/or side-swing openings.

The 440x540 oval cover must be ordered according to the tank diameter in steps from 0.1 to 0.2 in. If the tank diameter is between to steps, the higher diameter should be chosen,



TECHNICAL DATA


Certificate

3.1 (cover and frame are supplied with material certificate 3.1 according to EN10204)

Covers placed below liquid level

Cover shape	Type	Seal name	Function	Pressure
				Range* PSI
Oval	O-320X440IO	SO-320	Static tank	19
Oval	O-395X495IO	SO-550	Static tank	46
Oval	O-440X320IO	SO-320	Static tank	19
Oval	O-440X540IO	SO-540	Static tank	46
Oval	O-445X550IO	SO-550	Static tank	43
Oval	O-531X655IO	SO-655	Static tank	58

* Calculated max. pressure (PSI).



O-320x440IO O-395x495IO O-440x320IO O-440x540IO O-445x550IO O-531x655

PHYSICAL DATA

Materials

Steel parts: 1.4301 (304) or 1.4404 (316L)

Plastic parts: Nylon

Seal: EPDM, NBR, FPM or Silicone

Cover finish: Electropolished

Internal: Less Ra 32µin

External: Less Ra 32µin

Frame: Brushed

Internal: Less Ra 120µin

External: Less Ra 120µin

Alfa Laval reserves the right to change specifications without prior notification. ALFA LAVAL is a trademark registered and owned by Alfa Laval Corporate AB.

ESE02100ENUS 1507

© Alfa Laval

How to contact Alfa Laval

Contact details for all countries are continually updated on our website. Please visit www.alfalaval.us to access the information direct.