



### Material

Superstrut fittings and brackets are manufactured from hot rolled carbon steel.

### Dimensions

The following standard dimensions apply to all fittings except as indicated on the individual drawings.

Hole spacing	$1\frac{9}{16}$ " from end of fittings
Hole spacing	$1\frac{7}{8}$ " centers
Hole size	$\frac{9}{16}$ " diameter
Material	$1\frac{5}{8}$ " wide
Material	$\frac{1}{4}$ " thickness

### Application Instructions

Parts drawings illustrate a typical use for the fitting, and in many cases other uses for the part are appropriate.

### Design Data

Ratings vary when used with 12 or 14 gauge channel and are shown for each channel material.

GoldGalv® hardware finish is standard for all Superstrut products. This is a multi-process finish of electro-plated zinc, followed by gold colored zinc dichromate to give excellent corrosion resistance and a superior paint base. See pages B2–B3 for complete description of the GoldGalv® hardware finish. GoldGalv® hardware will be furnished if no other finish is specified.

### Nuts and Bolts Required

Unless otherwise noted, nuts and bolts for use with fittings and brackets should be ordered separately.

The standard bolt for the  $\frac{9}{16}$ " hole is a  $\frac{1}{2}$ " hex head cap screw  $1\frac{5}{16}$ " long. The  $1\frac{3}{16}$ " length may be used with all series channel.

Standard Finish – GoldGalv®, unless otherwise stated.