

Specifications

PFTP2500 PFTP3500

Trap Primer Valve



Product Features

- No adjustment or air pre-charge required
- Includes removable #60 mesh stainless steel conical filter screen
- Four view holes for easy inspection after installation
- Delivers potable water to seldom-used floor drains
- Pressure drop of 3 PSIG (20 Kpa) required to activate the priming valve
- Must be installed on cold fresh water lines of 1-1/2" diameter or less
- Operating range is 20 to 80 PSIG (138 to 552 Kpa)
- PFTP2500 primes up to 3 floor drains
- PFTP2500 is non-adjustable
- PFTP3500 primes up to 10 floor drains
- PFTP3500 is adjustable
- Machined of corrosion resistant (lead-free) brass
- Contains no springs or diaphragms.
- Metered amount of water from the floor drain trap primer is distributed to as many as ten (10) floor drain traps by means of the patented distribution units
- Distribution units are fully guaranteed on a money-back basis when installed per manufacturers' recommendations
- Can be connected to any cold water line, and will be automatically activated when a valve or faucet that is on the line is opened. A pressure drop of 3 psi will activate all of the trap seal primers
- Can be disassembled in the field and permits filter replacement without affecting the performance of the primer
- The "O" ring seals are tested for reliability at a temperature range of -40°F to 450°F

Description	No. Drains	Dist. Units
PFTP2500	3	PFTPDUU
PFTP3500	10	PFTPDUU

Parts

No.	Description	A (Inch)	B (Inch)	C (Inch)	D (Inch)	E (Inch)	Numbers of Drains Served
1	PFTP2500	4 1/8" (105)	3 1/4" (82)	7/8" (22)	1 1/4" (32)	1 1/8" (29)	3
2	PFTP3500	4 1/8" (105)	3 1/4" (82)	7/8" (22)	1 1/4" (32)	1 1/8" (29)	10



PFTP2500/PFTP3500

Warranty and Codes

This PROFLO product carries a 1-year limited warranty.

CALIFORNIA PROPOSITION 65 WARNING. This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

