

# MOEN®

# Specifications

## DESCRIPTION

- Duralock® quick connect installation
- Metal construction with various finishes identified by suffix
- 1/2" IPS connections
- Includes pop-up waste drain assembly

## OPERATION

- Lever style handles
- Hot side counterclockwise to open (clockwise to close)
- Cold side clockwise to open (counter-clockwise to close)

## FLOW

- Water usage is limited to these maximum flow rates as indicated by the corresponding product markings
  - 1.2 gpm max (4.5L/min) at 60 psi

## CARTRIDGE


- 1234 cartridge design
- Nonmetallic and stainless steel material

## STANDARDS

- Third party certified to WaterSense®, ASME A112.18.1/CSA B125.1 and all applicable requirements referenced therein
- Certified to NSF 61/9 & 372
- Products marked with 1.2 gpm are compliant with California water efficiency regulations
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- ADA ♿ for lever handles

## WARRANTY


- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
  - 10 year limited warranty when used in a multifamily installation
  - 5 year limited warranty when used in a commercial installation
- Visit [www.moen.com/support](http://www.moen.com/support) for complete details and limitations



**Seena™**  
**Two-Handle Widespread**  
**Lavatory Faucet**

**Models:** 5011 series

**NOTE:** This faucet is designed to be installed through 3 – 1 1/8" dia. holes, 4" on center.



## CRITICAL DIMENSIONS

(DO NOT SCALE)