

**Feature**


- 400# WOG
  - DZR lead free brass body
  - F1807 full port
  - Barb (F1807) x MNPT
  - PEX end (ASTM F1807)
  - Threaded end (ASME B1.20.1-NPT)
  - Chrome plated ball
  - Virgin PTFE seats
  - Blow-out proof stem
  - Double NBR O-ring packing
  - CSA B125.14
  - AB1953, NSF/ANSI 61 & 372 certified
- Option with wing handle (5006ABW) available



Pressure/ Temperature rating	
300 psi from 15 °F to 160 °F	150 psi max. at 200 °F

**Material**

	Part	Material	Specification
1	Body	DZR Lead Free Brass	ASTM B927 C27453
2	End piece	DZR Lead Free Brass	ASTM B927 C27453
3	Ball	DZR Lead Free Brass / Cr plated	ASTM B927 C27453
4	Seat	PTFE	PTFE
5	Stem	DZR Lead Free Brass	ASTM B927 C27453
6	O-ring	NBR	NSF approved
7	Handle	Steel / Dacromet® plated	ASTM A36
8	Handle nut	Steel / Zn plated	ASTM A36



**Dimension, Weight**

Size	T	A	H	L	P	C	Wt.
		[in]	[in]	[in]	[in]	[in]	[lb]
½"	½ - 14 NPT	2.39	1.38	3.19	0.35	0.61	0.28
¾"	¾ - 14 NPT	2.63	1.73	3.58	0.53	0.62	0.42
1"	1 - 11.5 NPT	3.19	1.85	3.58	0.71	0.77	0.64

