









Installation and User Guide



















Install the batteries and perform the door handing process

This step will teach your lock the orientation of your door and is crucial to lock operation.

Install 4 AA batteries in the battery pack.

With the door open, install the battery pack to initiate auto-handing.






The latch will retract and extend to learn the orientation of the door.

If the bolt does not move, make sure the batteries are correctly installed, and perform step 5B again. Note: The latch bolt will only retract half way.

The Status LED will indicate success or failure.




Green: Door handing was successful. Proceed to next step.

Red: Door handing was unsuccessful. Make sure the lock interior and batteries are correctly installed. Perform step 5B again.


If the door handing process is still unsuccessful after a second attempt, see the Manual Door Handing section on page 4.

Test the lock and check door alignment

With the door open, insert the key to extend the latch. Ensure that the latch extends smoothly.




Turn the key 180° to retract the latch. Ensure that the latch retracts smoothly.



Close the door. Insert and rotate the key to lock the door. Ensure that the door locks smoothly.



Turn the key 180° to retract the latch. Ensure that the door unlocks smoothly.




If your door does not lock and unlock smoothly, make sure you replaced your previous latch and strike with those supplied in the box. If you still experience locking errors, call Kwikset Support to order a Warped Door Service Kit.

Kwikset Support: 1-800-327-5625

Install the interior cover

Important Information about the interior cover

The window on the interior cover is unlocked by default for easier access to the battery pack and buttons.



For additional security, you may choose to lock the window by installing the security screw.





When the window is locked, you will need to remove the entire interior cover and screws to access the battery pack and buttons.

Lock

Bag




68611

(3x)

64109

Cover Installation









Battery Pack Access

If the window is unlocked, slide up the window to access the battery pack.



If the window is locked, remove the interior cover and screws to access the battery pack.



Download the app and create an account



1\ The Kwikset app is needed to use this lock. If this lock was professionally installed (or installed by someone other than the homeowner), make sure this step is performed by the homeowner.




Download the Kwikset app by scanning the QR code or visiting www.kwikset.com/app on your smartphone.



Create your account and follow the setup instructions in the Kwikset app.

Halo Keypad at a Glance



System Alerts


Alert	Reason	Solution
Keypad flashes red once with one beep*.	One incorrect code entered.	Re-enter code.
Keypad flashes red three times with three beeps*.	No user code programmed.	Program at least one user code.
Keypad flashes red 15 times with 15 beeps*	Three incorrect codes entered.	Re-enter code after 60 second keypad lockout.
Keypad flashes red with fast beeping sound for three to four seconds.	Low battery.	Replace batteries.
Keypad flashes red with continuous beeping sound for two seconds.	Door jammed while attempting to lock.	Manually re-lock door. If needed, reposition strike.
Lock beeps continuously.	Interior assembly is disconnected from exterior.	Remove battery pack, reconnect the interior to the exterior, then reinstall battery pack.

^{*}Beeping sounds will only be heard if Lock Sounds have not been disabled in the app.

Status LED colors

These features can be adjusted in some smart home apps.


The keypad will not light up if the door is unlocked.



Color	Lock Status	
Green (solid)	Action successful	
Green (blinking)	Unlocked	
Red (solid)	Door handing process unsuccessful	
Red (blinking)	Action unsuccessful or incomplete	
	Low battery	
Blue (solid)	Bluetooth Pairing successful	
Blue (blinking)	Bluetooth Pairing Mode	
Amber (solid)	Entering Network Reset mode	
Amber (blinking)	Network or System Reset mode.	
	Action required.	
	Locked	

Manual Door Handing

If needed, the door handing process can be initiated manually. This is useful if the lock is being moved to a different door.



Network Reset


Network Reset will delete all Wi-Fi settings, Bluetooth pairings, user associations, and remove the lock from the account.

1 Press and HOLD A" for 10 seconds. You will hear 1 short beep and see an amber LED.

Note: After 3 seconds, you will hear 1 short beep and see a blue LED. You should continue to hold "A" to enter network reset mode.

2 Release "A." You will see a blinking amber LED to indicate it is in network reset mode.

3 Press and release the Program button to confirm network reset.



The Program button must be within 10 seconds o releasing "A" or the function will time out.

Status 4 If successful, you will hear 1 long beep and see a green LED. If

unsuccessful, you will hear 5 rapid beeps and see a blinking red LED. If unsuccessful, repeat from step 1. Successful: Unsuccessful:





red

System Reset

System Reset will delete all access codes and lock settings including lock handing. The lock will run the handing process at the end of the System Reset.

1 Press "A" 10 times. You will hear 1 short beep and see a blinking amber LED to indicate it is in system reset mode.



2 Press and release the Program button to confirm system reset. Program button

 $3\,$ If successful, you will hear $1\,$ long beep and see a green LED, and the reset process will begin. During the reset process, the LED will blink green/red a few times and will beep when complete.

If unsuccessful, you will hear 5 rapid beeps and see a blinking red LED. If unsuccessful, repeat from step 1

Successful: Unsuccessful:

green red LED LED

Factory Reset


Factory Reset will delete all Wi-Fi settings, Bluetooth pairings, user associations, remove the lock from the account, and reset all lock settings including handing.

1 Remove battery pack.



2 Press and HOLD the Program button while reinserting the battery pack. Keep holding the button for 30 seconds until and the status

LED flashes red.



3 Press the Program button once more. The LED will flash green and red, and the auto-handing process will begin



4 The latch will retract and extend to learn the orientation of the door. The LFD will flash green if auto-handing is successful or red if autohanding is unsuccessful.

Important Safeguards

1. Read all instructions in their entirety.

- 2. Familiarize yourself with all warning and caution statements.
- 3. Remind all family members of safety precautions.
- 4. Protect your user codes.
- 5. Dispose of used batteries according to local laws and regulations.
- **WARNING:** This Manufacturer advises that no lock can provide complete security by itself. This lock may be defeated by forcible or technical means, or evaded by entry elsewhere on the property. No lock can substitute for caution, awareness of your environment, and common sense. Builder's hardware is available in multiple performance grades to suit the application. In order to enhance security and reduce risk, you should consult a qualified locksmith or other security professional.

Troubleshooting

A complete Halo Keypad Programming and Troubleshooting Guide is available at www.kwikset.com/halo/support

SmartKey Re-Keying

Re-key the lock to work with your existing key. See the supplied SmartKey Re-key instructions for more information.

Note: If Auto-Lock is enabled, remove the battery pack before re-keying your lock.

