



A CSW Industrials Company

PRODUCT DATA SHEET

COIL-CURE™

Evaporator coil cleaner and disinfectant

Description

Coil-Cure is a non-abrasive, one-step disinfectant cleaner designed specifically for HVAC equipment in homes, nursing homes, institutions, offices, schools, motels and hotels. Recommended for disinfecting and cleaning evaporator coils, HVAC catchpans, floors, walls and tabletops. Coil-Cure has been added to the EPA list N as an EPA Registered disinfectant with emerging viral pathogens AND human coronavirus claims for use against SARS-CoV-2.

READ ALL SDS, DIRECTIONS AND WARNINGS ON LABEL BEFORE USE

Directions for Use:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

DISINFECTION: To disinfect hard non-porous surfaces (such as HVAC catchpans and air conditioning evaporator coils), proceed as indicated below:

1. Shake can before using.
2. Hold six to eight inches from surface to be treated.
3. Spray area until it is covered with a white foam. Allow foam to penetrate and remain wet for 10 minutes. No scrubbing necessary.
4. Wipe off with a clean cloth, mop or sponge. This product will not leave grit or soap scum. For heavily soiled areas, remove gross soil before treatment.

MILDEWSTAT: To control mold and mildew on pre-cleaned, hard, non-porous surfaces (such as floors, walls, tabletops) spray surfaces to be treated, making sure to wet completely. Let air dry. Repeat application at weekly intervals or when mildew growth reappears.



Characteristics | Features

- EPA Reg. No. 44446-23-51219
- Disinfects against Canine Parvovirus
- Kills Legionella Pneumophila
- Effective via AOAC methodology against a wide variety of organisms
- Controls mold and mildew
- Cleans and deodorizes
- Cuts grease and grime without scrubbing
- No rinsing required

Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Feet
11070	18oz Aerosol	12	17.5	.58

Specifications

Wt/Gal @ 77°F: 8.34 lbs./Gal

Flash Point None

Color White Foam

Shelf Life 1 year

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.

Precautionary Statements

Refer to Safety Data Sheet (SDS).

KEEP OUT OF REACH OF CHILDREN**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC - DAY OR NIGHT 1-800-424-9300**

For additional Technical Information Call Toll Free 1-800-231-3345

Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RectorSeal, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by

RectorSeal, LLC**2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com**

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2021 RectorSeal. All rights reserved. R50400-0821