



**We Know Water.**

**VANDAL-RESISTANT, BARRIER-FREE  
VERSACOOLER® II WITH HANDS-FREE BOTTLE FILLER**  
• PGV8EBF • PGVEBF

**Suggested Specification**

Model PGV8EBF shall deliver 8.0 gph of 50°F water at 90°F ambient and 80°F inlet water per ASHRAE 18 testing. Model PGVEBF is a non-refrigerated fountain and delivers ambient water. Shall include the VersaFiller Sports Bottle Filler with hands free activation; lower unit shall have a single vandal resistant push button to activate the flow of water. VersaFiller components contain Freshield®, which utilizes a silver-based antimicrobial compound to protect the surfaces from discoloration, odors and degradation caused by the growth of microorganisms and mildew. Basin shall be designed to eliminate splashing and standing water. Water saver bubbler to reduce waste water by 50% and shall have flexible guard and operate between 20 and 100 PSI. Cabinet finish shall be brushed stainless steel. Cabinet shall have galvanized steel screens to prevent objects from being inserted into ventilation panels or underside of unit. Shall use R-134a refrigerant. Shall comply with ANSI 117.1 and ADA. Shall be listed by Underwriters Laboratories to US and Canadian standards. Shall comply with NSF/ANSI 61 and NSF/ANSI 372.



	PGV8EBF	PGVEBF
<b>Features:</b>	<ul style="list-style-type: none"> <li>Built-in 100 micron strainer stops particles before they enter the waterway</li> <li>Vandal resistant bubbler with flexible guard infused with silver-based antimicrobial additive</li> <li>Vandal resistant mechanical front push button</li> <li>Vandal resistant fasteners</li> <li>Galvanized steel louver and bottom screens</li> <li>Waterways are Lead-Free in materials &amp; construction</li> <li>Stainless steel top and heavy duty galvanized steel frame</li> <li>High efficiency cooling system</li> <li>Hands free VersaFiller with built in filter monitor and bottle counter</li> </ul>	
<b>Filtration:</b>	Option to add VersaFilter Filtration System	
<b>Power:</b>	115 Volts, 60 Hz	
<b>Activation By:</b>	Contactless Sensor on Bottle Filler and Manual Activation on Fountain	
<b>Mounting Type:</b>	Wall Mounted	
<b>Chilling Option:</b>	8.0 gph	Non-refrigerated
<b>Installation Location:</b>	Indoor	

**Installation**

- Prior to rough-in consult with local, state and federal codes for proper mounting height
- Shipped with complete instructions and wall mounting bracket. Removable side and front panels provide easy access for installation

**Finishes**

- Standard cabinet finish: Stainless steel

**Options**

- One piece chrome plated brass bubbler (036700-001)
- VersaFilter

**Limited 5-Year Warranty**

(Continental limits of the United States and Canada)

Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

**Export Warranty**

One year on components parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

**Certifications/Compliance**

- Certified to UL 399 and CAN/CSA C22.2 No.120 (electric water coolers only)
- Product Certified to NSF/ANSI Standard 61-G & 372 and conforms with the lead content requirements for "Lead Free" plumbing as defined by California, Vermont, Maryland, and Louisiana state laws and the U.S. Safe Drinking Water Act
- These water coolers comply with the requirements of ADA (Americans with Disabilities Act) when properly installed

**WARNING:**  
Cancer and Reproductive Harm  
www.P65Warnings.ca.gov

\*Industry standard rating condition 80°F inlet water temperature



Specifications subject to change without notice

