

Features

- No internal linkages, reducing the chance of clogs in the overflow pipe.
- Swivel-ball joint construction for easy installation.
- Includes toe-activated closing, and brass tee and pipe.
- For use with Elevance™, Archer™, Underscore®, Rêve™, and Parity™ baths and whirlpools.

Material

- Solid-brass construction.
- KOHLER finishes resist corrosion and tarnishing.
- Schedule 40 PVC overflow housing.

Installation

- Above- or through-the-floor.



Codes/Standards














ASME A112.18.2/CSA B125.2


KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	CP	Polished Chrome
	SN	Vibrant® Polished Nickel
	AF	Vibrant® French Gold
	PB	Vibrant® Polished Brass
	BGD	Vibrant® Moderne Brushed Gold
	G	Brushed Chrome
	BN	Vibrant® Brushed Nickel
	BV	Vibrant® Brushed Bronze
	2BZ	Oil-Rubbed Bronze
	BL	Matte Black
	RGD	Vibrant Rose Gold
	TT	Vibrant Titanium
	VNT	Vintage Nickel



Technical Information

All product dimensions are nominal.