

NLOPAC-R6509

6" AC Opal - LED Surface Mount

Source: 15W LED
1050lm

Type

Project

Catalog No.

Notes

PRODUCT DESCRIPTION

The AC Opal LED Series LED fixture is designed to surface mount over a standard junction box. The low profile dimmable luminaire produces even illumination and is cULus listed for wet locations.

FEATURES

- AC LED (No Driver)
- Dimmable
- 2700K, 3000K, 4000K or 5000K @ 90+ CRI
White, bronze or natural metal finishes
- Mount on standard 4" junction box
- ENERGY STAR certified

SPECIFICATION

Construction: One piece aluminum die formed housing and trim. Aluminum body dissipates heat and extends life.

Mounting: AC Opal (no driver) is flat on the back and suitable for installation on most 4" octagon boxes or 4/0 plaster ring. Luminaires can be installed in covered ceiling and wall mount. Luminaires can also be mounted on 5" or 6" recessed housings using optional torsion spring kit (NLOPAC-56RECKIT-2).

Optics: Nora specified and designed precision molded lens for optimal lumen output and even distribution.

Finishes: Available in white, bronze and natural metal finishes.

Ratings: IC rated when used with a 4" electrical junction box rated for direct contact with insulation. Fire rated when used with fire rated junction box.

ELECTRICAL

Input Voltage: 120V

Operating temperature: 0-45°C

Lumens / Wattage: 1050lm / 15W

Color Temperature: 2700K or 3000K

Color Rendering Index: 90+ CRI

Dimming: 5% with Triac or 10% with ELV

[Click Here](#) or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab

ACCESSORIES

NLOPAC-56RECKIT-2: Opal can be mounted on 5" or 6" recessed housings using optional torsion spring kit.


NLOPAC-4BKT-2: Universal bracket for mounting 6" Opal to 3" or 4" junction boxes.

LISTING

- cULus Listed for wet locations (covered ceiling only)
- ENERGY STAR certified
- [5-Year Limited Warranty](#)
- RoHS Compliant
- Suitable for use in closets when installed in accordance to NEC Section 410.16 (A)(1) and 410.16 (C)(1).



PRODUCT IMAGES AND DIMENSIONS



LTZ
Light Bronze



NM
Natural Metal



W
White



NLOPAC-56RECKIT-2
Retrofit Kit for 5" or 6" Recessed Housings



NLOPAC-4BKT-2
Universal Bracket for 3" or 4" Junction Boxes

6" AC Opal - LED Surface Mount

Color Temperature / Finish

NLOPAC-R650927ABZ = 2700K / Bronze (Discontinued, direct replacement: [NLOPAC-R6509T2427BZ](#))

NLOPAC-R650927ANM = 2700K / Natural Metal

NLOPAC-R650927AW = 2700K / White

NLOPAC-R650930ABZ = 3000K / Bronze (Discontinued, direct replacement: [NLOPAC-R6509T2430BZ](#))

NLOPAC-R650930ALTZ = 3000K / Light Bronze

NLOPAC-R650930ANM = 3000K / Natural Metal

NLOPAC-R650930AW = 3000K / White (Discontinued, direct replacement: [NLOPAC-R6509T2430W](#))

NLOPAC-R650940ABZ = 4000K / Bronze (Discontinued, direct replacement: [NLOPAC-R6509T2440BZ](#))

NLOPAC-R650940ANM = 4000K / Natural Metal (Discontinued, direct replacement: [NLOPAC-R6509T2440NM](#))

NLOPAC-R650940AW = 4000K / White (Discontinued, direct replacement: [NLOPAC-R6509T2440W](#))

NLOPAC-R650950AW = 5000K / White (Discontinued, direct replacement: [NLOPAC-R6509T2450W](#))

Optional Accessories

Description

NLOPAC-56RECKIT-2 = Retrofit Kit for mounting on 5" or 6" housings

NLOPAC-4BKT-2 = Universal Bracket for mounting to 3" or 4" j-box

Example: **NLOPAC-R650927AW** = 6" AC Opal, 1050lm / 15W, 2700K, White finish