



Defoamer

A fast-acting foam preventer for recovery tanks.

Features & Benefits

- Formula controls foam and stops build up of foam in auto scrubber and extractor tank, reducing time to refill extractor
- Protects extractor motor from damage from foam

Applications

- For use as a foam reducer in autoscrubber and extractor recovery tanks





Defoamer

Use Instructions

- Shake well before use
- Add 1 oz. of Defoamer to every 10 gal. capacity of recovery tank (30 mL per 37.8 L)
- For tools and hoses, pour approximately 1/2 oz. (15 mL) into tool or hose assembly
- Additional Defoamer may be used depending on amount of residuenin carpet

Caution: Do not allow product to get directly on to hard surface floors as it may leave the floor slippery. To remove product scrub the floor with detergent and dry thoroughly.

Technical data	Defoamer
Color/Form	Milky Cream, liquid
pH	8.25
Scent	Bland
Shelf Life	2 Years

Product	Pack size	Dilution	Product code	
Defoamer	6 x 32 oz. / 946 mL Squeeze Bottles	Ready-to-use	95002620	

Safe handling

Please make sure your employees read and understand the product label and Safety Data Sheet before using this product. The label contains directions for use; and both the label and SDS contain hazard warnings, precautionary statements and first aid procedures. SDS are available online at www.diversey.com or by calling 888.352.2249. Improper use or dilution may result in damage to surfaces and may result in health and physical hazards that match those of the concentrate. Please refer to the Diversey HazMat Library, only available through Internet Explorer, <http://naextranet.diversey.com/dot/>, for up-to-date shipping information.