



# SUBMITTAL INFORMATION

## Steel Coupling - (FC3-xxx-xx style)



### 1/2" THROUGH 8" STEEL COUPLINGS WITH DUCTILE IRON END RINGS



NOM. PIPE SIZE	PIPE O.D. (IN.)	SLEEVE LENGTH	CATALOG NUMBER	NUMBER OF BOLTS	BOLT DIA. & LENGTH	APPROX. WT. LBS.	✓ SUBMITTED ITEM(S)
1/2"	0.84	5"	FC3-084-5	2	1/2"x7"	2	
		7"	FC3-084-7	2	1/2"x9"	2	
3/4"	1.05	5"	FC3-105-5	2	1/2"x7"	2	
		7"	FC3-105-7	2	1/2"x9"	3	
		12"	FC3-105-12	2	1/2"x14"	3	
1"	1.32	5"	FC3-132-5	2	1/2"x7"	3	
		7"	FC3-132-7	2	1/2"x9"	3	
1-1/4"	1.66	12"	FC3-132-12	2	1/2"x14"	4	
		5"	FC3-166-5	2	1/2"x7"	4	
1-1/2"	1.90	7"	FC3-166-7	2	1/2"x9"	4	
		12"	FC3-166-12	2	1/2"x14"	5	
		5"	FC3-190-5	2	1/2"x7"	4	
2"	2.38	7"	FC3-190-7	2	1/2"x9"	5	
		12"	FC3-190-12	2	1/2"x14"	7	
		5"	FC3-238-5	2	5/8"x8"	7	
		5"	FC3-238-5-H	3	5/8"x8"	10	
		7"	FC3-238-7	2	5/8"x10-1/2"	10	
		7"	FC3-238-7-H	3	5/8"x10-1/2"	12	
2-1/2"	2.88	12"	FC3-238-12	2	5/8"x15"	13	
		12"	FC3-238-12-H	3	5/8"x15"	14	
		5"	FC3-288-5	3	5/8"x8"	10	
		7"	FC3-288-7	3	5/8"x10-1/2"	11	
		12"	FC3-288-12	3	5/8"x15"	14	
3"	3.50	24"	FC3-288-24	3	5/8"x27-3/8"	24	
		5"	FC3-350-5	4	5/8"x8"	16	
		7"	FC3-350-7	4	5/8"x10-1/2"	17	
		12"	FC3-350-12	4	5/8"x15"	26	
4"	4.50	24"	FC3-350-24	3	5/8"x27-3/8"	35	
		5"	FC3-450-5	4	5/8"x8"	16	
		7"	FC3-450-7	4	5/8"x10-1/2"	17	
		12"	FC3-450-12	4	5/8"x15"	27	
6"	6.63	16"	FC3-450-16	4	5/8"x20"	31	
		24"	FC3-450-24	4	5/8"x27-3/8"	38	
		5"	FC3-663-5	6	5/8"x8"	25	
		7"	FC3-663-7	6	5/8"x10-1/2"	31	
		12"	FC3-663-12	6	5/8"x15"	50	
8"	8.63	16"	FC3-663-16	6	5/8"x20"	65	
		24"	FC3-663-24	4	5/8"x27-3/8"	38	
		5"	FC3-863-5	6	5/8"x8"	34	
		7"	FC3-863-7	6	5/8"x10-1/2"	41	
		12"	FC3-863-12	6	5/8"x15"	51	
		16"	FC3-863-16	6	5/8"x20"	63	
		24"	FC3-863-24	6	5/8"x27-3/8"	78	

"-H" indicates Three Bolt Style

#### FEATURES

- Center Sleeve: Steel per ASTM A1011 with black Armorguard e-coat (exterior has an additional fusion-bonded epoxy coating)
- End Rings: Ductile iron (Grade 65-45-12) per ASTM A536 with red fusion-bonded epoxy coating
- Gaskets: NBR (Buna-N) per ASTM D2000  
Optional armor-tipped gaskets for conductivity are available, add "-ATG" to end of catalog number.
- Bolts and Nuts: High strength low alloy steel per ASTM A242. Optional Type 304 stainless steel available, add "-P" to end of catalog number.
- Rated Working Pressure: 300 psi

The Ford Meter Box Company considers the information in this submittal form to be correct at the time of publication. Item and option availability, including specifications, are subject to change without notice. Please verify that your product information is current.



#### The Ford Meter Box Company, Inc.

P.O. Box 443, Wabash, Indiana U.S.A. 46992-0443

Phone: 260-563-3171 / Fax: 800-826-3487

Overseas Fax: 260-563-0167

www.fordmeterbox.com

08/22/19

Submitted By: