SUPERSEDED OR VOID DATA

WE CAN ASSUME NO RESPONSIBILITY FOR USE OF

4






LOCATION

CLEANOUT PLUGS AND COVERS

TAPER THREAD PLUG WITH ROUND COVER

FUNCTION: Used in Female Pipe Size openings in Drainage piping where a cleanout is required. Countersunk plugs have slot sized to receive 1/2"(13) thick steel bar stock. Face-of-wall cover is desirable on finished walls.



COUNTERSUNK PLUG
Fig. 4470T LESS COVER AND SCREW
Fig. 4472T WITH COVER AND SCREW

Α	В		
SIZE	DIA		
0150(40), 02(50), 0250(65)	4 1/4(110)		
03(80), 0350(90), 04(100)	5 1/2(140)		
05(125)	7(180)		
06(150)	9 1/4(235)		
08(200), 10(250)	11 1/4(285)		

NOTE: Dimensions shown in parentheses are in millimeters.

REGULARLY FURNISHED:

Cast Bronze Taper Thread Plug with Stainless Steel Round Cover and Screw as indicated by Figure Number.

VARIATIONS:

Longer Screw (Specify Length)
"T" Handle Plug -TP

Plug tapped 1/4"(6) - 20 Thread
Vandal Proof Screw -U

OPTIONAL MATERIALS:

Polished Bronze Cover -PB
Prime Coated Steel Cover -PC
Stainless Steel Plug

(See Fig. 9775)

E DC B	1-11-96 7-27-94 6-15-94 7-30-93	Added Millimeters Submittal Update Chg'd Title Redrawn, Chg Var & update form	EMB EMB EMB TWK	BS BS BS BS	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 4470 4479
REV.	DATE	DESCRIPTION	BY	CKD. BY			1170, 1172

), 4472 | DRAWN BY: | CHECKED BY: | APPROVED BY: | DATE: | SCA BH JM 2-16-70 | SCA

AND CHANGE WITHOUT NOTICE