Gas Range, 36", 6 Burners, LPG

Series 7 | Professional

Stainless Steel | LPG



Professional style with power. 17,000 BTU gas burners paired with a large capacity gas oven.

- Top burner heat of 17,000 BTU, for seriously fast boiling
- Convection oven with 5.3 cu ft total capacity
- Non-tip full-extension shelves in main cavitiy for safe removal of hot dishes
- Made from quality materials and real stainless steel

DIMENSIONS

Height	35 3/4 - 36 3/4"
Width	35 7/8"
Depth	29 1/8″

FEATURES & BENEFITS

GENEROUS CAPACITY

Featuring a generous total capacity of 5.3 cu ft, with enough room to fit a 32 lb turkey and full-sized baking sheets.

COOKTOP POWER

Sealed Dual Flow Burners[™] deliver cooktop power up to 17,000 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

COOKING FLEXIBILITY

The cooktop is designed for easy access to any burner with grates you can smoothly slide pots across. The oven is large enough to hold full size baking sheets.

DESIGN QUALITY

This range has craftsmanship in every detail, with real stainless steel, cast-iron grates, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful legs to the powerful cooktop, the Range is built to last.

EASY TO CLEAN

Cleaning up spills is effortless with the continuous, porcelain basepan. Your cooktop simply needs a quick wipe to keep it looking good as new.

TOTAL CONTROL

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

SPECIFICATIONS

Accessories Square handle option AH-R36 Burner ratings Maximum burner power 17000 BTU Power back centre 13000BTU

Power back centre	13000BTU
Power back left	13000BTU
Power back right	13000BTU
Power front centre	15000BTU
Power front left	17000BTU
Power front right	17000BTU
Total cooktop power	88000 BTU

Capacity

Shelf positions	5
Shelf positions	5

Controls

Electric circuit	3 wire
Metal illuminated dials	•

Gas Requirements

Fitting and pipe	½ NPT, min. 5%" 🛛 flex line
Supply Pressure (LPG)	11" to 14" W.C

Oven features

Broil pan	•
Electronic oven control	•
Full extension telescopic	•

FISHER & PAYKEL

QUICK REFERENCE GUIDE > RGV3-366-L

Infrared Broiler	•	
Internal light	•	Recommen
Titanium coated, illuminated	•	Combustible
Oven functions		Non combu
		Recommend
Bake	•	
Broil	•	Safety
Convection bake	•	ADA compli
Number of functions	4	Full extension
Slow cook	•	
Oven performance		SKU
Bake power	21,500 BTU	
Broil power	19,000 BTU	The product dim and model. Unde
Power requirements		specifications ma Paykel's Custom
Amperage	15A	currently availab
Rated current	15A	
Supply frequency	60Hz	
Product dimensions		
Depth	29 1/8″	
Height	35 3/4 - 36 3/4"	
Width	35 7/8″	
Rangetop features		
Sealed Dual Flow Burners™	6	
Sealed range top	•	
Vent trim included	•	

ecommended Back Guards Ventilation combustible situation BGRV3-3036H lon combustible situation BGRV2-3036 / BGRV2-1236 tecommended hood HCB36-6_N (36" Professional afety . LDA compliant . tull extension telescopic . KU 82003

and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com

Э

↓

Service & Warranty

✓ Installation Guide



A PEACE OF MIND SALE

24 Hours 7 Days a Week Customer Support

T 1.888.936.7872 Wwww.fisherpaykel.com

FISHER & PAYKEL