



# MECHANICAL CLEANOUT PLUGS

## DWV TESTING MADE SIMPLE

- Quick & Easy – Mechanical Operation
- High Test Pressures - Up to 150 ft head/ 65 psi / 15 floors\*
- No Tools Required - Install / Remove in seconds
- Fits PVC, ABS, & Cast Iron Cleanout Tees
- Durable & Replaceable Rubber Pads
- 2 Stage Locking Mechanism - Locks into test & drain positions
- No Backsplash Draining

**TEST  
WINNER  
BEST™**



271038 shown



271148 shown



271058 shown

PART NUMBER	DESCRIPTION	MAXIMUM BACK PRESSURE	FLOW RATE
271128	2" Mechanical Cleanout Plug	150 ft head / 65 psi / 15 floors*	
271038	3" Mechanical Cleanout Plug	150 ft head / 65 psi / 15 floors*	
271048	4" Mechanical Cleanout Plug	100 ft head / 44 psi / 10 floors*	
271058	4" Mechanical Cleanout Plug with Fill/Drain	100 ft head / 44 psi / 10 floors*	Up to 9 GPM**
270308	2" Mechanical Cleanout Plug Replacement Pad Kit		
270318	3" Mechanical Cleanout Plug Replacement Pad Kit		
270328	4" Mechanical Cleanout Plug Replacement Pad Kit		
270338	4" Mechanical Cleanout Plug with Fill/Drain Replacement Pad Kit		
271148	Shut off Valve, Mechanical Cleanout Plug <i>(CALL FOR AVAILABILITY)</i>		

\*calculated using 10 ft head per floor \*\*calculated with pressure at 80 psi



Find us on

©2020 OateySCS. All Rights Reserved. This information is based on data believed to be reliable but Oatey makes no warranties, express or implied, as to its accuracy and assumes no liability arising out of its use. The data listed falls within the normal range of product properties but should not be used to establish specification limits or used alone as the basis of design. Oatey's liability to purchasers is expressly limited to the terms and conditions of sale. Oatey is a trademark of Oatey Co. Oatey Co. is part of the Oatey family of companies. All other trademarks can be found on Oatey.com.