



INDUSTRY'S MOST COMPLETE AIR MOVER LINE

THE WORLD'S LIGHTEST AND DURABLE AIR MOVER AND DRYER

XPOWER Centrifugal Air Movers are manufactured with a fully integrated housing, motor and parts design. This precision manufacturing allows for maximum balance, performance and efficiency. XPOWER offers a complete line of air movers to cover all drying requirements. Ranging in power from 1/8 HP to 1 HP, XPOWER has four different product groups – Series 200, 400, 600 and 800 – with a variety of models to suit every industry from restoration to janitorial and sanitation.



- Lightest and quietest air mover in the industry
- Powerful & energy efficient 138 Watts to 1 HP motor
- Compact, durable & rugged plastic housing models
- Multi-Angle positions for different drying and ventilating applications
- International safety certifications



XPOWER MANUFACTURE, INC
240 CLARY AVENUE, SAN GABRIEL, CA 91776
PHONE: (626) 285-3301 EMAIL: INFO@XPOWER.COM

WWW.XPOWER.COM

SPECIFICATIONS

AIR MOVER SERIES	MIGHTY MINI SERIES			400 SERIES	
MODEL NO.	P-80A	P-130A	P-230AT	400	430
VOLTZ/HERTZ	115V / 60 Hz	115V / 60 Hz	115V / 60 Hz	115V / 60 Hz	115V / 60 Hz
MOTOR	138 W	1/5 HP	1/4 HP	1/4 HP	1/3 HP
POWER	1.2A	2.0 A	2.3 A	3.0 A	3.8 A
RATED AIRFLOW	600 CFM	700 CFM	925 CFM	1600 CFM	2000 CFM
SPEEDS	3 Speed	3 Speed	3 Speed	3 Speed	3 Speed
CORD LENGTH	10 ft.	10 ft.	10 ft.	20 ft.	20 ft.
OPERATING POSITIONS	4	4	4	4	4
STACKABLE	Yes	Yes	Yes	Yes	Yes
3 HOUR TIMER	No	No	Yes	No	X-430TF
DAISY CHAIN	Yes	Yes	Yes	X-400A	No
FILTER KIT	No	No	No	OPTIONAL	X-430TF
UNIT WEIGHT	7.9 Lbs.	9.3 lbs	9.9 Lbs.	15 - 17.2 Lbs.	15 - 17 Lbs.
UNIT DIMENSIONS (LXWXH)	11.5" x 9.3" x 12.3"	10.7" x 12.4" x 13.3"	10.7" x 12.4" x 13.3"	13.9" x 14.8" x 14.6"	13.9" x 14.8" x 14.6"
HOUSING	PP	PP	PP	PP & ABS	ABS
SAFETY CERTIFICATIONS	ETL/CETL	ETL/CETL	ETL/CETL	ETL/CETL	ETL/CETL
DUAL THERMAL PROTECTION	Yes	Yes	Yes	Yes	Yes
PALLET QUANTITY	84 Units	72 Units	72 Units	45 Units	45 Units

AIR MOVER SERIES	600 SERIES		600 SERIES	
MODEL NO.	600	630	600	630
VOLTZ/HERTZ	115V / 60 Hz	115V / 60 Hz	115V / 60 Hz	115V / 60 Hz
MOTOR	1/5 & 1/3 HP	1/2 HP	3/4 HP	1 HP
POWER	1.5-3.8 A	5.0 A	7.5 A	8.5 A
RATED AIRFLOW	2400 CFM	2800 CFM	3200 CFM	3600 CFM
SPEEDS	3 Speed	3 Speed	3 Speed	3 Speed
CORD LENGTH	25 Ft.	20 Ft.	20 - 25 Ft.	20 - 25 Ft.
OPERATING POSITIONS	4	4	4	4
STACKABLE	Yes	Yes	Yes	Yes
3 HOUR TIMER	No	No	X-800TF	No
DAISY CHAIN	X-600A (GFCI)	No	No	No
FILTER KIT	Optional	Optional	X-800TF	Optional
CARPET CLAMP	Optional	Optional	Optional	Optional
TELESCOPIC HANDLE W/ WHEELS	No	No	P-800H (3 Position)	P-830H & X-830H (3 Position)
UNIT WEIGHT	21.5 Lbs.	18.7 - 21.9 Lbs.	23 - 27.6 Lbs.	24 - 28.5 Lbs.
UNIT DIMENSIONS (LXWXH)	15.9"x15.7"x16.3"	15.9"x15.7"x16.3"	15.9"x18.7"x18.7"	15.9"x18.7"x18.7"
HOUSING	PP & ABS	PP	PP & ABS	PP & ABS
SAFETY CERTIFICATIONS	ETL / CETL	ETL / CETL	ETL / CETL	ETL / CETL
DUAL THERMAL PROTECTION	Yes	Yes	Yes	Yes
PALLET QUANTITY	36 Units	24 - 36 Units	16 Units	16 Units

INDUSTRIES WE SERVE



ACCESSORIES:

