ASONRY BITS

2-CUTTER SDS MAX DRILL BITS

Diameter	Usable Length	Length	Part No.
3/8"	7"	13"	48-20-3901
1/2"	7"	13"	48-20-3902
1/2"	11"	17"	48-20-3903
1/2"	15"	21"	48-20-3904
1/2"	22"	28"	48-20-3905

Diameter	Usable Length	Length	Part No.
1/2"	30"	36"	48-20-3906
1/2"	54"	60"	48-20-3909
9/16"	7"	13"	48-20-3910
9/16"	15"	21"	48-20-3912



This product complies with ANSI B212.15 standard

4-CUTTER SDS MAX DRILL BITS

Diameter	Usable Length	Length	Part No.
5/8"	7"	13"	48-20-3916
5/8"	11"	17"	48-20-3917
5/8"	15"	21"	48-20-3918
5/8"	30"	36"	48-20-3922
5/8"	54"	60"	48-20-3923
11/16"	15"	21"	48-20-3926
3/4"	7"	13"	48-20-3930
3/4"	11"	17"	48-20-3931
3/4"	15"	21"	48-20-3932
3/4"	30"	36"	48-20-3936
13/16"	16"	21"	48-20-3938
27/32"	16"	21"	48-20-3942
7/8"	8"	13"	48-20-3944
7/8"	12"	17"	48-20-3945
7/8"	16"	21"	48-20-3946
7/8"	31"	36"	48-20-3949
1"	8"	13"	48-20-3952
1"	12"	17"	48-20-3953
1"	16"	21"	48-20-3954

Diameter	Usable Length	Length	Part No.
1"	31"	36"	48-20-3956
1-1/16"	18"	23"	48-20-3958
1-1/8"	12"	17"	48-20-3964
1-1/8"	16"	21"	48-20-3966
1-1/8"	31"	36"	48-20-3967
1-1/4"	10"	15"	48-20-3970
1-1/4"	18"	23"	48-20-3972
1-1/4"	31"	36"	48-20-3974
1-3/8"	12"	17"	48-20-3975
1-3/8"	18"	23"	48-20-3980
1-3/8"	31"	36"	48-20-3983
1-7/16"	18"	23"	48-20-3984
1-1/2"	12"	17"	48-20-3986
1-1/2"	18"	23"	48-20-3988
1-9/16"	18"	23"	48-20-3990
1-5/8"	18"	23"	48-20-3991
1-3/4"	18"	23"	48-20-3992
2"	18"	23"	48-20-3993



This product complies with ANSI B212.15 standard

SDS MAX VACUUM BITS

OVERVIEW

The MILWAUKEE® SDS Max Vacuum Drill Bits reduce airborne silica dust and provide increased productivity during the chemical anchor preparation process. The combination of dust extraction holes at the bit tip and the hollow shaft design allow dust to be removed through the bit while drilling holes, reducing airborne silica dust in the process. SDS Max Vacuum Drill Bits are an OSHA® Table 1 compliant solution when used with dust extraction vacuums. Additionally, SDS Max Vacuum Drill Bits leave clean holes which are ready for the chemical anchor installation, removing the need to use standard drill bits with the "blow-brush-blow" cleaning method, delivering up to 2X faster chemical anchor preparation. The 4-Cutter tip design delivers durability in concrete and concrete with rebar applications. The universal adapter fits most common dust extractor attachments.







FEATURES

- Drilling holes into brick, block, concrete, and concrete with rebar
- Preferred Table 1 solution for the OSHA® Regulation on Crystalline Silica Dust (29 CFR 1926.1153), when used with a dust extractor
- Up to 2X faster chemical anchor preparation

SDS MAX VACUUM BITS

JDJ IIIAA VAOOOIII DITJ			
Diameter	Usable Length	Length	Part No.
5/8"	15-3/4"	23-1/2"	48-20-2152
3/4"	15-3/4"	23-1/2"	48-20-2156
7/8"	15-3/4"	23-1/2"	48-20-2160
1"	17-1/2"	25-1/4"	48-20-2164
1-1/8"	27-1/2"	35"	48-20-2168
1-3/8"	27-1/2"	35"	48-20-2172



This product complies with ANSI B212.15 standard

SDS MAX VACUUM BITS ADAPTER

Description	Part No.	
SDS Max Vacuum Bits Adapter	48-20-2150	

48