

Features

- Stationary spout.
- 10" (254 mm) spout reach.
- 1.2 gpm (4.5 lpm) maximum flow rate at 60 psi (4.14 bar).
- Drain sold separately.
- Coordinates with other products in the Components™ collection.

Material

- Brass construction.
- KOHLER finishes resist corrosion and tarnishing.

Required Products/Accessories

- K-77980-4 Wall-mount bathroom sink faucet handle
or
K-77980-4A Wall-mount bathroom sink faucet handle
or
K-T77981-4 Wall-mount bathroom sink faucet trim
or
K-T77981-8 Wall-mount bathroom sink faucet trim
or
K-T77981-9 Wall-mount bathroom sink faucet trim

Recommended Products/Accessories

- K-23726 Drain treatment
K-23723 Faucet cleaner

Optional Products/Accessories

- K-7107 Decorative Drain
K-7108 Decorative Drain
K-7114 Pop-Up Drain
K-7124 Pop-Up Clicker Drain
K-7127 Drain
K-7129 Drain



ADA CSA B651 OBC

Codes/Standards

ASME A112.18.1/CSA B125.1
NSF/ANSI 61
NSF/ANSI 372
All applicable US Federal and State material regulations
DOE - Energy Policy Act 1992
EPA WaterSense®
California Energy Commission (CEC)
ADA
ICC/ANSI A117.1
CSA B651
OBC


KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.

Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	CP	Polished Chrome
	BN	Vibrant® Brushed Nickel
	BL	Matte Black



Technical Information

All product dimensions are nominal.

Faucet:

Flow rate: 1.2 gal/min (4.5 l/min)

Pressure: 60 psi (4.1 bar)

Drain included: No

Spout:

Spout reach: 10" (254 mm)

Notes

Install this product according to the installation instructions.

ADA, OBC, CSA B651 compliant when installed to the specific requirements of these regulations.