



# Stealth AV3000 Airmover

High velocity, long-throw airflow. Ventilates smoke, dust and fumes and dries large spaces fast. Direct air anywhere – easily reposition the airmover on its versatile integrated stand. The Stealth's advanced blade design delivers quieter operation AND higher intensity airflow. Variable speed control for easy airflow adjustments.



## FEATURES

- Integrated stand provides ultimate control - direct airflow at walls, floors or ceilings
- Low-noise Stealth™ fan blades for quieter operation
- Variable speed to customize airflow and noise levels
- Power outlet socket for daisy-chaining – up to four units on a single 15A circuit
- Hour meter
- Circuit breaker and reset switch
- Secure, nested stacking – up to 5 high
- Rugged carry handle and integrated cord wrap

## SIZES ▪ OPTIONS

- **113164 (F568):** One unit

## SPECIFICATIONS

- **Air movement:** 2600 CFM | 4417 CMH
- **Static pressure (H2O):** 0.40 in. | 99 Pa
- **Circuit maximum:** Up to 4
- **Dimensions (D × W × H):** 10.8 × 24.3 × 24.0 in. | 27.4 × 61.7 × 61.0 cm
- **Weight:** 27.5 lbs. | 12.5 kg
- **Amps:** 2.7A
- **Volts:** 115V
- **Frequency:** 60Hz
- **Power:** 0.46HP / 340W (motor rating)
- **Sound level (avg.):** 58–72 dB
- **Control:** Variable speed rotary switch
- **Cord length:** 15 ft. | 4.6 m
- **Construction:** Rotomolded polyethylene and injection molded ABS housing components; steel wire inlet and outlet grills.
- **Safety:** ETL listed to UL/cUL and CSA Standards
- **Xactimate:** WTRDRY+