



Revolution LGR

Compact, stackable and easy to transport, the Revolution's space-saving design and state-of-the-art technology lets you bring high performance drying power to every task. Its i-Series smart controller delivers maximum performance in all conditions. Rugged rotomolded housing and durable construction ensure long life.



FEATURES

- Small, light Xactimate “Large” category dehu – more water removal than units 2–3 times its size!
- Delivers “Large” dehu performance yet fits where others don’t – crawlspaces, bathrooms, kitchens, etc.
- Control panel displays inlet and outlet temp and RH plus grain depression in real time
- Secure, compact stacking – transport multiple units on a handtruck
- Fastest access for cleaning and maintenance
- Fit more drying in the truck, make fewer trips – make more profit!

SIZES - OPTIONS

- 111995 (F413): One unit

SPECIFICATIONS

- **Water removal:** 80 pts./day | 38 L/day at 80°F/60%RH (AHAM)
139 pts./day | 66 L/day at 90°F/90%RH
- **Air movement:** 121–180 CFM | 206–306 CMH
- **Dimensions (W × H × D):** 12.5 × 17.6 × 21.5 in. | 31.8 × 44.7 × 54.6 cm
- **Housing:** Rotomolded polyethylene
- **Weight (w/cord & hose):** 65 lbs. | 29.5 kg
- **Amps:** 6.2A (at 80°F/60%RH)
- **Volts:** 115V
- **Frequency:** 60Hz
- **Sound level (ave.):** 55 dB
- **Operating range:** 33°F–100°F | 1°C–38°C
- **Air filter:** 4-PRO filter
- **Safety:** ETL listed to CSA standards
- **Xactimate:** WTRDHM>L