Specifications

ARM2215

15G Engineered Yarn A2 PU Dipped Glove











ANSI/ISEA 105







Product Features

- · Polyurethane Palm Coating
- · 15 Gauge Engineered Yarn Liner
- · ANSI A2 Cut Level
- · Touch Sensitivity
- · Low Particulate Shed
- · Liner: Ultra-High-Molecular-Weight Polyethylene Yarn
- · Coating: Polyurethane
- · Cuff: Engineered Yarn and Latex Elastic

| SPECIFICATIONS | | | | | |
|----------------|------|--|--|--|--|
| SKU | Size | | | | |
| ARM2215S | 7 | | | | |
| ARM2215M | 8 | | | | |
| ARM2215L | 9 | | | | |
| ARM2215XL | 10 | | | | |

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

Packaging

- ·1 Pair on Hangtag
- ·12 Pairs in Polybag
- · 120 Pairs in Case





Testing Performance

ANSI/ISEA 105

| Cut | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
|----------|---|---|---|---|---|---|---|---|---|
| Abrasion | 1 | 2 | 3 | 4 | | 6 | | | |
| Puncture | 1 | 2 | 3 | | 5 | | | | |

EN388

| L11000 | | | | | | |
|--------------------|---|---|---|---|---|---|
| Abrasion | 1 | 2 | 3 | | | |
| Circular Blade Cut | 1 | 2 | 3 | | 5 | Χ |
| Tear | 1 | 2 | 3 | 4 | | |
| Puncture | 1 | 2 | 3 | 4 | | |
| Cut TDM-100 | Α | В | С | D | Е | F |
| Impact Rated | Р | F | | | | |